

说明书

版式设计要求：

1. 字体：标题为Myriad Pro SemiBold，内容为 Myriad Pro light；
2. 上下页边距为9mm，左右边距为8mm；；
3. 标注说明书长宽尺寸，单位mm。

WaterdrOp

In-Line refrigerator filter

Model: WD-INL



Tested and Certified by NSF International against **NSF/ANSI Standard 42** in model EFF-6035A for the reduction of the claims specified on the Performance Data Sheet, and to **NSF/ANSI 372 (≤0.25% lead)**.

Compatibility

Compatible with refrigerators, dispensers, ice makers, RVs, motor homes, boats, and so on.

Accessories list

- a. Filter
b. 1/4" compression and push-to-connect fitting (adapter fitting)
c. 1/4" compression hex nut, sleeve, and insert
d. 1/4" PE tubing
e. Clips and screws
f. Cable tie mounts and cable ties

Installation instructions (Take refrigerator as an example)

Step 1

Turn off the refrigerator water supply valve and turn on the refrigerator dispenser to ensure that there is no residual water.


Step 2

Remove the refrigerator water supply pipe from the refrigerator joint and connect the pipe to the adapter fitting. Wrap some Teflon tape on the external thread while connecting.




Step 3

Connect the adapter fitting to the filter inlet. (The inlet is on the cap side with "IN".)




Step 4

Take out the 1/4" PE tubing, install the hex nut, sleeve, and insert in the proper order. Connect the 1/4" PE tubing to the refrigerator joint. Wrap some Teflon tape on the external thread while connecting and then tighten it with a wrench.




Step 5

Put a bucket or basin at the filter outlet, open the water supply valve, and flush the filter for 5 minutes. It is normal to see black water while flushing.



Step 6


Connect the 1/4" PE tubing to the filter outlet.





Step 7

Select suitable fittings to fix the filter.

Option 1-Bracket: Select the proper position on the cabinet wall and install the bracket. Then push the filter into the bracket.




Option 2-Cable tie mounts: Take out 4 cable tie mounts and select the proper position on which to paste them. Then thread the cable ties into the cable tie mounts to fix the filter.



Other installation situations

A: If an inline water filter has been installed before and is connected to the braided stainless steel hoses, remove the hoses from your original filter's inlet and outlet. Insert two adapter fittings into the inlet and the outlet of our filter. Screw the braided stainless steel hoses on the adapter fittings.



B: If an inline water filter has been installed before and is connected to 1/4" PE pipes with quick-connect fittings, remove the tubes from your original filter's inlet and outlet. Connect 1/4" PE pipes to our filter.



Frequently asked questions:

Q: What should I do if water leaks at the connection after installing the filter?

A: Turn off the cold water valve and check the water leakage. 1) If the water leakage is at the connections between the refrigerator water supply pipe and the adapter fitting, wrap some Teflon tape on the adapter fitting; 2) If the water leakage is at the connection at the inlet of the refrigerator, tighten the hex nut, sleeve, insert, and refrigerator joint with a wrench; 3) If the water leakage is at the inlet or outlet of the filter, make sure the PE tubing and adapter fitting are inserted to the end.

Q: Why does the water sometimes smell bad?

A: Bacteria can easily grow in the water when you are on vacation or do not use the filter for several days. When you use it again, you will need to flush it for a while before you drink, to drain the internal deposited water.

Q: Does the filter need to be flushed after installation?

A: Yes, it is recommended that you turn on the faucet and flush the filter for 5 minutes after installation. The filter media has coconut shell activated carbon, so you may see black water while you flush.

Warning:

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions.
1. This filter unit must be replaced every 12 months.

2. Do not use this product at temperatures under 32°F/0°C. Otherwise, the product will freeze. Failure to follow instructions and operating specifications will void your quality assurance. Further, the manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

*The service life mentioned above is subject to chlorine reduction. Actual result varies according to the local water quality.

Performance data sheet

System Model No.: **EFF-6035A**

Operating specifications:

Operating Temperature: 33 ~100°F/0.6 - 38°C
Working Pressure: 20 ~100 psi/140 - 689 kPa
Rated Capacity: 1,400 gallons/5,300 litres
Flow Rate: 0.5 gpm/1.9 lpm

Substance reduction:

The system has been tested and certified by the NSF International according to NSF/ANSI Standard 42 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for the water leaving the system, as specified by NSF/ANSI Standard 42. While testing was performed under standard laboratory conditions, actual performance may vary.

Substance	Inf. Average	NSF Specified Challenge Concentration	Ave. % Reduction(%)	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.1 mg/L	2.0mg/L±10%	97.6%	0.05mg/L	N/A	≥50%	J-00356469



Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)
E-mail: FRG@waterdropfilter.com



图像颜色请依据数码稿印刷
请不要擅自变更来稿件，如须修改，请联系伊可普做有关决定

印刷品技术要求 IMPORTANT PRINTING CAUTION

1. 印刷要求 ☐覆光膜 ☐覆亚膜 ☐UV油 ☐吸塑油 ☐过油 ☐丝印
2. 材质要求 80g双胶纸，双面印刷
3. 颜色要求 单黑印刷
4. 版面要求 印刷品文字线条印迹清晰、无重影;印刷品套印准确无偏色、溢墨、指痕等;印刷品上光层均匀、光亮、牢固无粘连;覆膜表面平整、无褶皱、光泽度好;纸张材质正确，切边整齐、压线深浅适中、洁净、无斑点和条痕。



青岛伊可普电器有限公司包材设计图纸

品牌 BRAND NAME.		工厂型号 ITEM NO.	EFF-6035
物料编码 INNER CODE.	03070206035CS	版本号 VERSION.	V050
包材文件名称 FILE NAME.	03070206035CS WD-INL-42-说明书-V050		
规格 MEASURE.	210*140mm	页数 PAGE.	4P
设计负责人 DWG.BY	张鑫龙	审核日期 VERIFY DATE.	
变更描述 DESCRIPTION.	2021.12.13 1. 增加客服24H7D365信息 2024.5.10 更改邮箱 LOGO		