

WHITE

WHITE

WHITE

WHITE

WHITE



®

100% SILICONE

CONTIENE: Destilados de petróleo, etiltriacetoxisilano y metiltriacetoxisilano. Se genera ácido acético durante el período de curado. Evite el contacto con los ojos, la piel y la ropa. Puede causar irritación en los ojos, piel y tracto respiratorio. Dañino si se traga. Evite respire los vapores. Utilice en un área bien ventilada. Cerciórese de que exista entrada de aire fresco. Use guantes y gafas de seguridad. Retire los lentes de contacto antes de utilizar el producto. **PRIMEROS AUXILIOS:** PIEL: Lávese con agua y jabón. No utilice solventes ni limpiadores abrasivos para retirar el producto de la piel. OJOS: Enjuague inmediatamente con abundante cantidad de agua. INHALACIÓN: Trasládese al aire fresco. INGESTION: NO INDUZCA EL VÓMITO. Obtenga atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame al centro de control de envenenamiento al 1-800-222-1222. Consulte la Hoja de datos de seguridad (HDS) para más información. Para obtener una HDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.

QUESTIONS?/¿PREGUNTAS?
Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com & click on "Ask the Expert."

DAP Products Inc.,
Baltimore, MD
21224

Made in the USA
for DAP Products
Inc. with U.S.
and globally
sourced
materials.

dap.com

Silicone

ALL PURPOSE 100% SILICONE

100% WATERPROOF & WEATHERPROOF

- Flexible
- Minimal Shrinkage
- Lifetime Guarantee
- Interior/Exterior

Window, Door, Siding & Trim

WARNING! CONTACT WITH UNCURED PRODUCT MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. Read back panel carefully for other cautions.

¡ADVERTENCIA! EL CONTACTO CON PRODUCTOS NO CURADOS PUEDE CAUSAR IRRITACIÓN EN LOS OJOS, LA PIEL Y LAS VIAS RESPIRATORIAS. Lea cuidadosamente el panel posterior para otras precauciones.

9.8 fl oz (290 mL)

100% SILICONE

Meets the ASTM C920 requirements for Grade NS, Class 25. Uses A, O and NT.

FOR BEST RESULTS: Apply when surface temps are between -35°F to 140°F. Not recommended for continuous underwater use, surface defects, tuck-pointing, chimneys, stovepipes or fireplace applications. Corrodes some metals. Not for oily woods or cementitious surfaces. Joint width should not exceed 1/2". If joint depth exceeds 1/2", use foam backer rod. **Not paintable.** Store below 90°F in a dry place.

INSTRUCTIONS: 1. Prepare a clean, dry surface. 2. Cut nozzle at 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load into caulk gun. 5. Fill gap with sealant. 6. Smooth bead. 7. Allow at least 12 hours before exposing sealant to water. Do not touch or clean sealant for 24 hours. 8. Clean up excess uncured sealant from surface & tools with mineral spirits. Excess cured sealant must be cut or scraped away. Wash hands with soap & water.

COVERAGE: 53 linear ft at 3/16" diameter bead.

CONTAINS: Petroleum distillates & methyltriacetoxysilane. Acetic acid is evolved during cure. Avoid contact w/ eyes, skin & clothing. May cause eye, skin and respiratory tract irritation. May be harmful if swallowed. Do not ingest. Avoid breathing vapors. Use only w/ adequate ventilation. Ensure fresh air entry. Wear gloves & safety glasses. Remove contact lenses before using product. **FIRST AID:** SKIN: Wash thoroughly w/ soap & water. Do not use solvents or abrasive cleansers to remove product from skin. EYES: Immediately flood w/ large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

CCCS Calif. ARB VOC <3 wt/wt% (VOC 30 g/L)
WARRANTY: DAP will provide replacement product or refund sales price if product fails to perform when used as directed, within one year of the purchase date. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.