



6455 Drive-Maxx™ 1000 Premium Filler & Sealer

DRIVE-MAXX™ 1000

- ClimaSeal Technology, apply 45°F to 99°F
- Advanced Gel, Faster & E-Z to apply
- Fast Dry, foot Traffic Ready in 1 Hour*
- Urethane enhanced, delivers longest life
- UV protected, stays black longer

*Light foot traffic only - no vehicles for 24 hours

Black Jack Drive-Maxx 1000 is the best quality rubberized blacktop filler and sealer designed for asphalt pavements. This product renews the look of old worn driveways, and contains sand particles to fill in small cracks. Drive-Maxx 1000 is enhanced with a latex polymer to give maximum performance, unmatched durability and the best looking finish. The combination of Gel and Fast Dry Technology provide a fast and easy installation, plus the ability to open your driveway to foot traffic in just one hour (in good drying conditions). Drive-Maxx 1000 with ClimaSeal technology accelerates drying time and also allows for product to cure in cooler temps down to 45°F. Under normal drying conditions, (temperatures above 75°F, clear sunny skies, and humidity below 35%) this driveway sealer can be open to foot traffic in just 1 hour after application. (For vehicle traffic, you must allow minimum of 24 hours for product to completely cure.)

SURFACE PREPARATION: Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer season prior to application of any sealer. Driveways should be pressure washed before sealcoating. For oil stains, apply a degreaser (or dish soap) and scrub into surface to penetrate oil spots. This will promote proper bonding and will help prevent adhesion failures. Repair cracks and holes with Black Jack Speed-Fill Elastic Crack Filler for longest lasting results. Use Black Jack Speed-Patch for cracks and holes larger than 1". For larger potholes, use Ready Road Repair Permanent Pot Hole Patch (allow 6 weeks to cure). All repaired areas must be allowed to cure. See product instructions for curing times.

APPLICATION: Turn all pails upside down the night before, or at least prior to sealcoating. This product can be applied when temperatures are 45°F and rising, however, best results occur in warmer temperatures. **Do not apply if rain or cold temperatures below 45°F overnight are expected within 36 hours.** This sealer is not recommended or warranted for use on surfaces with slopes greater than 20°. Clean driveway thoroughly and rinse. Remove puddles and then apply sealer to a slightly damp surface (not wet). A small amount of water separation in the pail is normal and should be easily mixed in. Mix and pour out 1/3 of the container and spread product across the blacktop surface with a squeegee. Squeegee must be used to spread product and for proper application rates. After application with squeegee, a follow up with a brush may be used if a textured surface is desired. Complete the entire driveway in one continuous application to prevent "color shading". If multiple pails are used, it is best to match batch codes and blend the end of one pail with the other.

NOTE: Thick coats will result in uneven coverage, tracking and drying problems. Apply two uniform coats. Apply the second coat perpendicular to the first, after the first coat has cured (approx. 2 - 4 hours). Driveway must cure approx. 1 - 2 hours for foot traffic and 24 - 48 hours for vehicle traffic. Humid or cloudy conditions may prolong curing time. **Two thin coats are required.**

COVERAGE RATE: Approximate Coverage Rate (per coat) for 4.75 gallon pail: 350 sq/ft on smooth driveways, 300 sq/ft. on rough/worn driveways. Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed.

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

PRECAUTIONS: Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Dispose of in an environmentally acceptable manner, if not for yours, than for your children's sake. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. Caution should be taken on linoleum floors, which may experience slight discoloration from household traffic stains, including asphalt driveway sealers. Consult your linoleum manufacturer for suggestions. **KEEP FROM FREEZING.** Do not use in drinking water or food systems.

PRODUCT INFO & PERFORMANCE CHARACTERISTICS

Product Code	6455-9-30
Unit Size	5 gal.
Unit Dimensions	12" x 12" x 14.75"
Fill Level	4.75 gal. / 18 L
Unit Weight	49 lbs.
Upc	027134645556
Application Temperature:	45°F and rising
Color:	Brown liquid / Dries Black
Number of Coats Required	2 Uniform Coats

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 10 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**

FOR WARRANTY PURPOSES, PLEASE RETAIN YOUR RECEIPT ALONG WITH THE BATCH CODES FROM THE PRODUCT USED DURING APPLICATION. BLACK JACK DRIVE-MAXX BATCH CODES MAY BE FOUND ON THE LIDS OF EACH CONTAINER.