

## 1100LB 48V ELECTRIC HYDRAULIC DUMP CART

### ITEM NUMBER

OPD811

21

### UPC

826518005722

### DESCRIPTION

With a wet bucket for sand, gravel, concrete and more, the DK2 POWER OPD811 self-drive electric powered hydraulic dump cart runs for up to 6 hours on one charge with its 48V 20Ah battery and moves it all. Equipped with a hydraulic electric lift, this unit is capable of tipping its wet bucket 90 degrees vertically for easy unloading.

The OPD811 comes with throttle bar speed control and articulated floating rear wheels to keep your load level and steady. Moving around the job site is effortless with forward and reverse speeds of 6 MPH and dual front wheel drive to climb over rough terrain.

### SPECIFICATION

<b>BATTERY</b>	48V 20Ah (4 x 12V series)
<b>PAYLOAD CAPACITY</b>	1,100 lb (499 kg)
<b>DRIVE WHEELS &amp; TIRES</b>	All-terrain 4.00-8 Ø16" (Ø40.6cm) OD
<b>REAR WHEELS &amp; TIRES</b>	Off-road 4.10-4 Ø10" (Ø25.4cm) OD on Ø5" (Ø12.7 cm) rims
<b>MAX SPEED</b>	6 mph (9.7 km/h)
<b>RUN TIME</b>	6 hrs
<b>CHARGE TIME</b>	5 hrs
<b>BUCKET</b>	8 ft³ (0.23 m³), 45 gal (170.3 L), sealed steel
<b>DIMENSIONS</b>	60" (L) x 40" (W) x 40" (H) 152.4 cm (L) x 101.6 cm (W) x 101.6 cm (H)
<b>WEIGHT</b>	572 lb (259 kg)
<b>SHIPPING DIMENSIONS</b>	54" (L) x 34" (W) x 32" (H) 137.2 cm (L) x 86.4 cm (W) x 81.3 cm (H)
<b>SHIPPING WEIGHT</b>	616 lb (279.4 kg)
<b>WARRANTY</b>	1-year limited



### FEATURES

- Powered by a 48V 20Ah battery **1**
- 8 ft³ (0.23 m³) 45 gal (170.3 L) sealed steel wet bucket **2**
- All-terrain 4.00-8 Ø16" (Ø40.6 cm) OD front wheel drive tires, with electric drive up to 6 mph (9.7 km/h) and off-road 4.10-4 Ø10" (Ø25.4 cm) OD rear tires on Ø5" (Ø12.7 cm) rims to move effortlessly around job sites **3**
- Hydraulic electric lift cylinder to tip bucket to 90° vertical for easy unloading **4**
- Throttle bar speed control with articulated floating rear wheels keep your load level and steady
- Improved "magic brake" system to brake upon the release of the brake handle, making your hauls safe and secure **5**