

JOB NAME:

CONTRACTOR:

DATE:

PROFIT



WIRE STRIP COLLATION FOR FRAMING NAILS

TYPES

Clipped
Head



Smooth


Ring

Offset
Round Head



Smooth

Ring



FUNCTION

For general construction framing, sub-flooring, roof sheathing, deck, and fence building
Fits most 28° framing nailers

FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
Smooth Shanks provide lower withdrawal strength when compared to ring shanks
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength

CORROSION

Brite finishes offer little to no corrosion protection
Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards
300-series Stainless Steel is suitable for all marine applications

CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

TECHNICAL	Length x Dia	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	Nails per Strip	ASTM F1667 Bend Yield*
	2 x .113	6d	11.5	Ø 0.266 in	1.13 in	25	100,000 psi
	2-3/8 x .113	-	11.5	Ø 0.266 in	1.25 in	25	100,000 psi
	2-1/2 x .131	8d	10.25	Ø 0.281 in	1.25 in	25	100,000 psi
	3 x .120	10d	11	Ø 0.281 in	1.50 in	25	100,000 psi
	3 x .131	10d	10.25	Ø 0.281 in	1.50 in	25	100,000 psi
	3-1/4 x .120	12d	11	Ø 0.281 in	1.50 in	25	100,000 psi
	3-1/4 x .131	12d	10.25	Ø 0.281 in	1.50 in	25	100,000 psi
	3-1/2 x .131	16d	10.25	Ø 0.281 in	1.50 in	25	100,000 psi
	3-1/2 x .120	16d	11	Ø 0.281 in	1.50 in	25	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

WIRE STRIP COLLATION FOR FRAMING NAILS

TYPES

Clipped
Head



Smooth

Ring

PROFIT



PRODUCT	Size	Box Count QTY	Brite sku	EG sku	HDG sku	304 SS sku	316 SS sku
Smooth	2 x .113	2000	629130	-	636130	-	-
Smooth	2-3/8 x .113	2000	629150	-	636150	633150	-
Smooth	2-1/2 x .131	2000	629153	-	-	-	-
Smooth	3 x .120	2000	629171	-	636171	633171	-
Smooth	3 x .131	2000	629170	-	636170	-	-
Smooth	3-1/4 x .120	2000	629181	-	636180	-	-
Smooth	3-1/4 x .131	2000	629180	-	636181	-	-
Smooth	3-1/2 x .120	2000	629192	-	-	-	-
Smooth	3-1/2 x .131	2000	629190	-	636190	-	-
Ring	2 x .113	2000	629135	-	634130	-	-
Ring	2-3/8 x .113	2000	630150	-	634150	-	-
Ring	3 x .120	2000	630171	-	634170	-	-
Ring	3-1/4 x .120	2000	-	-	634180	-	-
Ring	3-1/2 x .120	2000	-	-	634190	-	-

TYPES

Offset
Round Head



Smooth

Ring

PRODUCT	Size	Box Count QTY	Brite sku	EG sku	HDG sku	304 SS sku	316 SS sku
Smooth	2 x .113	2000	629230	-	-	-	-
Smooth	2-3/8 x .113	2000	629250	-	636250	-	-
Smooth	2-1/2 x .131	2000	-	-	-	-	-
Smooth	3 x .120	2000	629271	-	636271	-	-
Smooth	3 x .131	2000	629270	-	-	-	-
Smooth	3-1/4 x .120	2000	629281	-	-	-	-
Smooth	3-1/4 x .131	2000	629280	-	-	-	-
Smooth	3-1/2 x .120	2000	-	-	-	-	-
Smooth	3-1/2 x .131	2000	629290	-	636290	-	-
Ring	2-3/8 x .113	2000	630250	-	634250	-	-
Ring	3 x .120	2000	630271	-	634270	-	-
Ring	3-1/4 x .120	2000	-	-	634280	-	-
Ring	3-1/2 x .120	2000	-	-	634290	-	-