Adds a borescope function to your security camera tester for inspecting behind walls and hard-to-reach areas

8150 Features:

- 8MP tester (1080p) with HDMI, BNC, and RJ45 ports
- Works with IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265
- WiFi for connecting to WiFi cameras and to create a WiFi hotspot
- Has PoE (24W) and DC power output (12V/3A)
- · Auto-recognize HD coax camera type and resolution
- · RJ45 TDR cable test and cable quality test
- UTP cable test detects opens, shorts and miswires
- 4 hour run time with 2-3-hour charge
- · Compact and lightweight
- Includes SBR2M Security Camera Borescope accessory, 7.4V Li-ion battery, AC adapter/charger, DC power cable, BNC cable, RS485 cable, audio cable, wrist strap and carrying case

SBR2M Borescope Features:

- Waterproof (IP67) 8mm camera (Lens only)
- 8mm lens diameter with 2m cable (6.5t)
- · 6 adjustable LEDs with thumbwheel control
- Power provided by the camera tester (12V 1/2/3A)
 no batteries needed
- · Utilizes the display resolution of your camera tester
- Image snapshot and Video record functions
- · Compatible with most camera testers

Applications:

Designed for the maintenance and installation of IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265. The 1920 x 1200 resolution enables it to display network HD cameras and analog cameras in high resolution.

Borescope for inspecting behind walls and hard-toreach areas; checking cable connections on the back of installed equipment; Insect or rodent infestation; Anywhere you need to see underneath and behind difficult to move objects

Ordering Information:

8150-BR-KIT CamView IP Pro 5 HD CCTV Camera Tester with Borescope SBR2M Security Camera Tester Borescope, 2M



Specifications

opcomeations	8150
8MP AHD	\checkmark
8MP TVI	\checkmark
8MP CVI	\checkmark
4k IP / Analog	\checkmark
Wifi	Connect to WiFi cameras & create a WiFi hotspot
HDMI Output (1080p)	√
DC 12V 3A Power Output	
48V PoE Output	
Advanced UTP cable test	\checkmark
Power	Rechargeable 7.4V 3350mAh Li-ion battery
Dimensions	7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm)
Weight	11.3oz (320g)
	SBR2M
Camera	8mm
Field of View	60°
Depth of View	1.2 to 4" (3 to 10cm)
Cable Length	2m (6.5ft)
Resolution	640 x 480
Illumination	6 adjustable LEDs
Still Image Capture	dependent on camera tester
Video Recording	dependent on camera tester
Power	12V 1/2/3A (provided by camera tester)
Interface	BNC
Dimensions	Camera & Cable: 6.5ft x 0.3" (2m x 8mm)
	LED Thumbwheel: 2x0.5x0.25" (51x13x6.4mm)
Weight	5.6oz (159g)



