



The Armor All/STP Products Company  
39 Old Ridgebury Road  
Danbury, CT 06810  
Tel. 1-203-205-2900

# Material Safety Data Sheet

<b>I Product:</b> ARMOR ALL® WHEEL PROTECTANT																	
<b>Description:</b> CLEAR, COLORLESS, THIN LIQUID WITH A MILD SOLVENT ODOR IN AN AEROSOL CAN																	
<b>Other Designations</b>	<b>Distributor</b>	<b>Emergency Telephone Nos.</b>															
	The Armor All/STP Products Company 39 Old Ridgebury Road Danbury, CT 06810	For Medical Emergencies call: 1-866-949-6465. For Transportation Emergencies call: 1-800-424-9300 (Chemtrec).															
<b>II Health Hazard Data</b>		<b>III Hazardous Ingredients</b>															
May cause mild eye and skin irritation. Prolonged inhalation of propellant may cause symptoms of central nervous system depression including headache, dizziness, nausea, loss of balance, and drowsiness.  No medical conditions are known to be aggravated by exposure to this product.  <u>FIRST AID:</u>  <u>EYE CONTACT:</u> Rinse with plenty of water. If irritation persists, call a doctor.  <u>SKIN CONTACT:</u> Wash with soap and water. If irritation persists, call a doctor.  <u>INGESTION:</u> Drink a glassful of water. Immediately call a doctor or poison control center.  <u>INHALATION:</u> Remove to fresh air. If breathing problems develop, call a doctor.		<table border="1"><thead><tr><th>Ingredients</th><th>Concentration</th><th>Worker Exposure Limit</th></tr></thead><tbody><tr><td>Decamethylcyclpentasiloxane CAS # 541-02-6</td><td>40 - 60%</td><td>Not established.</td></tr><tr><td>Triethoxyoctylsilane CAS # 2943-75-1</td><td>1 - 5%</td><td>Not established.</td></tr><tr><td>Propane CAS # 74-98-6</td><td>5 - 10%</td><td>1000 ppm - TLV-TWA<sup>a,b</sup> 1000 ppm - PEL<sup>c</sup></td></tr><tr><td>Isobutane CAS # 75-28-5</td><td>35 - 50%</td><td>1000 ppm TLV-TWA<sup>a,b</sup></td></tr></tbody></table> <p><sup>a</sup>TLV-TWA = ACGIH Threshold Limit Value-Time Weighted Average <sup>b</sup>ACGIH TLV-TWA for aliphatic hydrocarbon gases (C1-C4 alkanes) <sup>c</sup>PEL = OSHA Permissible Exposure Limit - Time Weighted Average</p> <p>None of the ingredients in the product are on the IARC, NTP, or OSHA carcinogen lists.</p>	Ingredients	Concentration	Worker Exposure Limit	Decamethylcyclpentasiloxane CAS # 541-02-6	40 - 60%	Not established.	Triethoxyoctylsilane CAS # 2943-75-1	1 - 5%	Not established.	Propane CAS # 74-98-6	5 - 10%	1000 ppm - TLV-TWA <sup>a,b</sup> 1000 ppm - PEL <sup>c</sup>	Isobutane CAS # 75-28-5	35 - 50%	1000 ppm TLV-TWA <sup>a,b</sup>
Ingredients	Concentration	Worker Exposure Limit															
Decamethylcyclpentasiloxane CAS # 541-02-6	40 - 60%	Not established.															
Triethoxyoctylsilane CAS # 2943-75-1	1 - 5%	Not established.															
Propane CAS # 74-98-6	5 - 10%	1000 ppm - TLV-TWA <sup>a,b</sup> 1000 ppm - PEL <sup>c</sup>															
Isobutane CAS # 75-28-5	35 - 50%	1000 ppm TLV-TWA <sup>a,b</sup>															
<b>IV Special Protection and Precautions</b>		<b>V Transportation and Regulatory Data</b>															
<u>Hygienic Practices:</u> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.  <u>Engineering Controls:</u> Use general ventilation to minimize exposure to product vapor.  <u>Personal Protective Equipment:</u> Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.  Contents under pressure. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. Store in accordance with NFPA 30B for Level 3 aerosols.		<u>DOT:</u> Consumer Commodity ORM-D.  <u>IMDG:</u> Aerosols, flammable, n.o.s., Class 2.1; UN1950; limited quantity.  <u>IATA:</u> Aerosols, flammable, n.o.s., Class 2.1; UN1950.  <u>EPA - SARA Title III/CERCLA:</u> This product is regulated under Sections 311/312. This product contains no chemicals that are regulated under Section 313 or under Section 304/CERCLA.															
<b>VI Spill Procedures/Waste Disposal</b>		<b>VII Reactivity Data</b>															
<u>Spill Procedures:</u> Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.  <u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state, and local regulations.		Stable under normal use and storage conditions.															
<b>VIII Fire and Explosion Data</b>		<b>IX Physical Data</b>															
<u>Flashpoint:</u> 79°C (closed cup) for liquid  <u>Flame extension:</u> 14 inches with flashback.  <u>Fire Extinguishing Agents:</u> Dry chemical, carbon dioxide (CO <sub>2</sub> ), foam, or water spray.  <u>Fire and Explosion Hazards:</u> Containers may rupture at temperatures >120°F.  <u>NFPA Aerosol Classification:</u> Level 3.  <u>CPSC Aerosol Classification:</u> Flammable.		pH..... N/A  Specific gravity ..... ~0.96  Solubility in water ..... Slight															