

Smart Vent 430 Andbro Drive, Unit 1 • Pitman, NJ 08071
Website: www.smartvent.com Tel: (877) 441-8368 Email: info@smartvent.com



Trim & Sleeve Kits

Trim and sleeve kits fit into the rough opening in order to provide a clean, finished look on the interior wall. They are available for all compatible models including multi-frame units.

NOTE: Trim & Sleeve kits are not available for Garage Door Models

STANDARD MODELS

FOR 16" x 8" VENTS (2 PIECE)

Standard finish: | 316L Stainless Steel

WOOD WALL MODELS FOR 14.5" x 8.5" VENTS (1 PIECE)

Standard finish: Powder Coat White

1540-531-12 kits adjustable from 7" - 12.5"

• 1540-531-15 kits adjustable from 10" - 15.5"

- 1540-573 4" wall depth
- 1540-573-9 9" wall depth

Fire Dampers

Our two Fire Damper models are UL Certified to provide 2 or 3hrs of fire resistance. They are intended to be used when flood vents are being installed into a fire rated wall. Available for models up to a 2 x 3 configuration.

A fusible link holds a galvanized steel door in place. At 165° F, the link melts to permit the door to drop, blocking the path of the fire.

NOTE: Trim flange and inner sleeve are required for installation, as well as an 8" minimum wall thickness.

STANDARD 16" x 8" MODEL

• 1540-530 2 or 3 hour fire resistance available


STANDARD 14.5" x 8.5" MODEL

1540-537 2 or 3 hour fire resistance available



Smart Vent Products, Inc. offers all of their flood vents in Stainless Steel, Standard Powder Coat Paint Colors of: White, Wheat, Gray, or Black, but can be custom color matched to your project's needs.





Smart Vent 430 Andbro Drive, Unit 1 • Pitman, NJ 08071 Website: www.smartvent.com Tel: (877) 441-8368 Email: info@smartvent.com