



# Multi-Purpose Medium Sheen Sealer

## A PREMIUM MULTI-PURPOSE LOW GLOSS ACRYLIC SEALER

### DESCRIPTION

Classic Multi-Purpose is a water-based acrylic, single-component, medium sheen sealer. It can be used over stains, polymer-modified cement toppings, waterborne colorants, concrete, brick, Spanish tile, slate, stucco and more. Its zero VOC formula ensures a safe application environment with minimal odor, prioritizing both user and environment safety. Suitable for both interior and exterior use, it can be used in a wide range of climates. It acts as a water repellent and is UV stable, which means it will not yellow over time. Ideal for those seeking low maintenance and easily cleanable surfaces, our sealer offers unmatched convenience. Its environmentally friendly composition, coupled with excellent adhesion and durability, ensures peace of mind. It is easy to use, affordable, and cleans easy with just soap and water. **Caution: slippery when wet. Add (CGG12oz) Classic Gator Grip to combat slipperiness. New concrete must cure for 28 days before applying sealer.**

### COVERAGE:

1 gallon (3.8 Liters)  
covers approximately  
300 sq. ft. to 450 sq.ft.  
depending on surface

### PACKAGING:

Available in 1 gallon jugs,  
5 gallon pails and  
55 gallon drums.

### STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

### SHELF LIFE:

2 years

### COLOR:

Milky, Dries Clear

Visit us online:

[ClassicCoatingsSystems.com](http://ClassicCoatingsSystems.com)

Visit our Youtube channel  
for How-to Videos and our  
Instagram for inspiration!



@classiccoatingsystems /classiccoatingsystems  
@simplestains

### ADVANTAGES

Water resistant
Waterborne: VOC 0 g/l, no fumes and low odor
High UV stability
Low cost, easy to apply, and low maintenance
Excellent adhesion and durability
Excellent hot tire pick-up after 7 days when applied over acid stain
Easy to clean with soap and water

### LIMITATIONS

May reflect working cracks in substrate
Recommended application temperature should be between 55° F and 95° F
Must be installed over a clean dry surface
Not freeze thaw and not for use under water
Not for use over water base stains on driveways
Surface must not contain moisture and efflorescence
If using high performance tires we recommend using a 2 part polyurethane sealer

### TYPICAL USAGE

- Over acid stain on driveways
- Pool Decks
- Walkways
- Stained concrete
- Restoration projects
- Architectural toppings
- Concrete floors
- Block walls
- Patios
- Masonry
- Spanish Tile
- Stucco
- Some Natural Stone

- Brick
- Flagstone
- Slate

\* Do not apply on driveways that have been stained with water based stains. Instead, we recommended using:

- CW404 Wet Look Water Base Sealer
- CW408 Matte Water Base Sealer

REVISED: July 2024

Classic Coatings Systems • 255 Citation Circle, Corona, CA 92878

© 2015 Classic Coatings Systems Inc. All rights reserved.



# Multi-Purpose Medium Sheen Sealer

## A PREMIUM MULTI-PURPOSE LOW GLOSS ACRYLIC SEALER

### PREPARATION

#### ✓ READ SDS BEFORE HANDLING & APPLICATION

- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ Caution: Surface is slippery when wet.
- ✓ New concrete must cure for 28 days before sealer is apply.

### INSTALLATION

1. Prepare surface by thoroughly removing all trace of any foreign matter.
  2. Mix well before use. Apply 1st coat with a brush, 3/8" nap roller, or pump sprayer. Sealer appears milky but dries clear. System thickness 1-2 wet mils. per coat. Do not allow the sealer to puddle as it will result in a white haze.
  3. After 30 to 60 minutes, repeat step (2) for the 2nd coat.
  4. A 3rd application may be required in high traffic areas.
- Cure time at 77°F: Dry to touch: 30 mins - Light foot traffic: 12 hrs - Full cure: 7 days

### MAINTENANCE

Over time, the sealer may wear down, particularly in areas with high traffic. It is advisable to reapply the sealer to areas where the sealer has worn down.

**For interior only:** Apply two coats of sealer to protect the undercoat of the sealed surface. May be buffed with a sky blue pad. No more than 3 coats. Use annually if needed.

**For exterior only:** Clean with water. Improper maintenance will result in wearing out your surface. If this occurs, use Classic Strip Away to remove sealers and stains in order to re-apply desired stain and sealer. Note that Classic Strip Away will remove any coats of sealers and stains on your surface.

### PHYSICAL CHARACTERISTICS & TECHNICAL DATA

- Coverage per liquid gallon 300-450 sq ft per gallon
- VOC 0 g/l
- Degree of Gloss – Very Low

It is HIGHLY recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

### PRODUCT AVAILABILITY & TECHNICAL ASSISTANCE

Technical assistance and information is available by calling:

(951) 279-2600

[www.classiccoatingsystems.com](http://www.classiccoatingsystems.com)

#### HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

#### PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

#### WARRANTY:

Classic Coatings products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.