to 100 gallons of diesel fuel. When temperatures drop below 0°F. or when using biodiesel blends, add entire contents (32 ounces) to 50 gallons of diesel fuel. If your vehicle will not start or gain power in cold temperatures, use Power Service Diesel 911® (red bottle) as directed on the container. After the engine is running. add Diesel Fuel Supplement +Cetane Boost.

This product is to be added to the fuel. DO NOT ADD TO THE DIESEL EXHAUST FLUID TANK.

## HANDLING PRECAUTIONS:

This product is packaged in a single-use container with a tamper-evident seal. Once the seal has been broken, the container cannot be resealed and will leak. Do not store previously opened containers in your vehicle. Clean up spills immediately.

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and nonroad engines.

DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED OR INHALED. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. MAY CAUSE SKIN, EYE AND RESPIRATORY IRRITATION. Use only in well-ventilated area. Keep away from heat and flame. Do not swallow. Do not breathe vapors. Avoid contact with skin and eyes. Wear protective gloves. FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If on skin, wash with soap and water. If in eyes, rinse slowly and gently with water for 15 minutes, removing contact lenses, if present, after the first 5 minutes. If inhaled, move to fresh air. If irritation persists for any exposure, call a physician. AWARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov. Contains petroleum distillates, hydroxy alkoxylate and aromatic hydrocarbons. KEEP OUT OF REACH OF CHILDREN.

Winterization

Go to powerservice.com to learn more about our year-round maintenance schedule.

POWER SERVICE PRODUCTS, INC. Weatherford, TX 76086 www.powerservice.com © 2018 Power Service Products, Inc.

Part No. 1025

1025 V

2