TOTO®

LT477(G)(MT)

Kiwami[®] Asymmetrical Vessel Lavatory

FEATURES

- 18-1/8"W x 16-1/2"D x 5-1/8"H
- CEFIONTECT[®] ceramic glaze minimizes debris and mold from sticking to surface (#01 only)
- CLEAN MATTE finish achieves a smoother surface that makes dirt removal easier while improving design (#CMW only)
- Crafted with LINEARCERAM[®]– a durable material for an ultra sleek and modern design
- Drain and decorative drain cover (sold separately)
- Complete with installation template
- ADA compliant
- Front overflow

MODELS

- LT477G#01
 With CEFIONTECT
- LT477MT#CMW With CLEAN MATTE WHITE finish (Available Q1 2020)

COLORS/FINISHES

- #01 Cotton
- #CMW CLEAN MATTE WHITE (Available Q1 2020)

PRODUCT SPECIFICATION

This vessel lavatory shall be made with LINEARCERAM. Lavatory shall be ADA compliant. Lavatory shall be TOTO Model LT477_____.

CODES/STANDARDS

- Meets ADA guidelines and ANSI A117.1 requirements when top of lavatory rim is installed 864mm (34") from finished floor and lavatory is installed 52mm (2-1/16") minimum from front edge
- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), State of Massachusetts , City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others







REQUIRED COMPONENTS FOR TOTO FAUCET

Drain (Kick Lever) and

Decorative Cover Plate (Sold Separately)

 THP737#01 / THP737#CMW for ZL: TLP02307U#XX GO: TLG01307U#XX GR: TLG02307U#XX GS: TLG03305U#XX

Decorative Cover Plate (Sold Separately)

 THP739#01 / THP739#CMW for ZA: TLP03301U#XX GE: TLG07305U#XX GC: TLG08305U#XX GM: TLG09305U#XX GB: TLG10305U#XX GF: TLG11305U#XX

Kiwami[®] Asymmetrical Vessel Lavatory

SPECIFICATIONS

Waste	1-1/4"
Size	18-1/8"W x 16-1/2"D x 5-1/8"H
Basin	19-3/8"W x 14-5/8"D
Basin Depth	5-1/8"
Warranty	One Year Limited Warranty
Material	LINEARCERAM®
Shipping Weight	17.5 lbs
Shipping Dimensions	17-3/4" x 17-3/4" x 7-3/4"

INSTALLATION NOTES

Recommended drains , THP737 or THP739. No drain is included. The recommended faucet height from deck to spout is 8-5/16" (211m) and below. Aim water supply away from the drain cover.

DIMENSIONS



These dimensions and specifications are subject to change without notice