

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DRYLOK LATEX BASE MASONRY WATERPROOFER – ALL COLORS
PRODUCT CODE: 651, 652, 655, 657

HMS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: UNITED GILSONITE LABORATORIES
ADDRESS: 1396 JEFFERSON AVENUE
SCRANTON, PA 18509

EMERGENCY PHONE: (800) 424-9300
INFORMATION PHONE: (570) 344-1202
NAME OF PREPARER: R. BARAKO

DATE REVISED: FEBRUARY 2005
SUPERSEDES: OCTOBER 2001

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mmHg@TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
WATER	7732-18-5	NOT ESTAB	NOT ESTAB	NOT ESTAB	1.0 (68F)	25
*DIETHYLENE GLYCOL MONO-METHYL ETHER	111-77-3	NOT ESTAB	NOT ESTAB	NOT ESTAB	0.1 (68F)	<5
BUTYL BENZYL PHTHALATE	85-68-7	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	<5
STYRENE ACRYLIC RESIN	25036-16-2	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	10
TITANIUM DIOXIDE	13463-67-7	15 MG/M ³	10 MG/M ³	NOT ESTAB	N/A	<5
LIMESTONE	1317-65-3	15 MG/M ³	10 MG/M ³	NOT ESTAB	N/A	20
CRYSTALLINE SILICA	14808-60-7	.1 MG/M ³ (1)	.1 MG/M ³ (1)	NOT ESTAB	N/A	25
MICA	12001-26-2	20 MPPCF	3 MG/M ³	NOT ESTAB	N/A	5
WOLLASTONITE	13983-17-0	NOT ESTAB	10 MG/M ³	NOT ESTAB	N/A	<5
FULLERS EARTH	8031-18-3	5 MG/M ³	10 MG/M ³	NOT ESTAB	N/A	<5

(1) Time Weighted Average

* Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 F

VAPOR DENSITY: HEAVIER THAN AIR

COATING VOC: 1.30 LB/GAL (156 G/L)

SOLUBILITY IN WATER: SOLUBLE

APPEARANCE AND ODOR: WHITE OR COLORS, PRODUCT SPECIFIC. TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O =1) 1.5

EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINERS MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

METHOD USED: N/A

LOWER: 1.7% UPPER: 22.0%

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, HEADACHE, NAUSEA, MENTAL CONFUSION, SLURRED SPEECH DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? NO
IARC CONCLUDES THAT THERE IS SUFFICIENT EVIDENCE IN HUMANS AND EXPERIMENTAL ANIMALS FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA IN THE FORMS OF QUARTZ OR CRISTOBALITE. IARC (GROUP 1) SEE SECTION II

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: GIVE ONE OR TWO GLASSES OF WATER. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS DO NOT GIVE ANYTHING BY MOUTH. CONSULT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVISE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH SOLID PARTICULATE CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE CHEMICAL SPLASH GOGGLES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM. WASH CONTAMINATED CLOTHING BEFORE REUSE

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.