# **ASSEMBLY INSTRUCTIONS**




- ◆ Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- ◆ Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.



If you need further assistance, please contact us by Email: customersupport@superiordecorinc.com

# **TOOLS REQUIRED**



#### HARDWARE INCLUDED



**Fixture** 





Circle











Screws




Wire Nuts

Shade


Washer Ball Nuts A Ball Nut B

\*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE




# **INSTALLATION** STEP 1

- 1. Unscrew the washer and ball nut from the mounting unit.
- 2. Adjust threaded rod on mounting unit to allow **fixture** to rest flush against the ceilin when ball nut is tightened.
- 3. Use the mounting screws to attach the mounting unit to the junction box (not included).




# STEP 2

Disassemble the decorative circle and shade under the **fixture** by unscrewing **ball nuts A**.




### STEP 3

Make the electrical connection from the junction box (not included) to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Next, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape.




# STEP 4

Secure the **fixture** to the **mounting unit** with



# STEP 5

Select the color temperature you need.



### STEP 6

Use the ball nuts A to attach the shade and decorative circle to the fixture.

