


ASSEMBLY AND INSTALLATION INSTRUCTIONS

W0274

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.


NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. Read and save these instructions.



Turn off the power at fuse or circuit box.

1. Attach the Cross Bar to the Wall Box by using (2) 1-1/4" Screws.

1a. Adjustable Fixture Screws - loosen the nut, adjust length as necessary, and tighten back down.




2. Make wire connections with wire connectors:

A - Connect the black wire from Fixture to the black wire from power source.

B - Connect the white wire from Fixture to the white wire from power source.

C - Attach the fixture grounding wire to the Cross Bar with the green grounding screw. Then connect it to the house grounding wire with a wire connector.

Carefully put wires back into the Wall Box.



3. Attach the Fixture to the Cross Bar through Screw Holes as shown, and secure with Bolt Nuts.

4. Attach the glass Shades to the Fixture, and secure them with the Socket Rings.

5. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.

Turn on the power at fuse or circuit box.

 VAXCEL

171023