



Keep It Clean!

Protects environment & equipment from the dispersion of oils and/or hydrocarbons



Elevator/Vault System





Independently verified by OnSpeX, div. of CSA, when installed in accordance with our instructions Applications include elevator sumps, transformer vaults and manufacturing facilities.


MODEL 57

MODEL 152/153

MODEL 161







See FM2778 (Model 57) FM2784 (Models 152/153), FM2785 (Model 161) for complete pump specifications

CHOOSE A PREPACKAGED SYSTEM


Part Number	Description	Alarm Panel	Oil Smart® Pump Switch	Nonautomatic Pump	Pump Part Number	Volts	НР	Amps	Elevator System
940-0005	Oil Guard® Pump Switch and Panel	10-1526	10-1528	N57	57-0002	115	3/10	9.7	N
940-0006	Oil Guard® Pump Switch and Panel	10-1526	10-1528	N152	152-0002	115	4/10	8.5	N
940-0007	Oil Guard® Pump Switch and Panel	10-1526	10-1528	N153	153-0002	115	1/2	10.5	N
940-0008	Oil Guard® Pump Switch and Panel	10-1526	10-1528	N161	161-0002	115	1/2	15.0	N
940-0012	Oil Guard® Pump Switch and Panel	10-1526	10-1528	*N152	*152-0028	115	4/10	8.5	Υ
940-0013	Oil Guard® Pump Switch and Panel	10-1526	10-1528	*N153	*153-0027	115	1/2	10.5	Υ
940-0014	Oil Guard® Pump Switch and Panel	10-1526	10-1528	*N161	*161-0090	115	1/2	15.0	Υ

^{* 6&#}x27; (1.8 m) SO jacketed cord for oil resistance.

OR BUILD YOUR OWN SYSTEM

Part Number	Description	Alarm Panel	Oil Smart® Pump Switch	Oil Smart® High Liquid Alarm Switch	Oil Smart [®] High Liquid Switch
10-1526	Oil Smart® Alarm Panel	√		V	
10-1528	Oil Smart® Pump Switch		√		
10-1727	Oil Smart® Pump Switch w/o Plug		√		
10-2149	Oil Smart® Simplex Panel	V	√	V	
10-2150	Oil Smart® Duplex Panel	√	√	V	√
10-2516	Oil Smart® Simplex Panel w/ Mtr.	√	V	*	

 $[\]sqrt{\,}$ INCLUDED * VARIABLE LEVEL FLOAT SWITCH



Simplex Panel

- 115V, single phase
- NEMA 4X watertight enclosure w/ lockable latch
- 30 amp motor start relay
- Pump HOA switch
- Top-mounted red alarm beacon light
- 81 84 decibel rated alarm horn
- Horn silence and alarm test switches
- Alarm automatically resets
- Dry auxiliary alarm contacts
- Separate circuit protection for alarm
- Circuit breaker protection
- Pump "Run" indicator light



Model 10-2149

Duplex Alternating Panel

- 115V, single phase
- NEMA 4X watertight enclosure w/ lockable latch
- (2) 30 amp motor start relays
- Pump HOA switches
- Top-mounted red alarm beacon light
- 81 84 decibel rated alarm horn
- Horn silence and alarm test switches
- Alarm automatically resets
- Dry auxiliary alarm contacts
- Separate circuit protection for alarm
- Pump "Run" indicator light



Model 10-2150