

SUPER SEAL™

SMOOTH PATCH



Shallow Asphalt Patch

- Black, Rubberized, Cement-Like Mix
- Asphaltic Adhesive, Self Bonding Formula
- Trowels To A Feather-Edge Finish

**SHALLOW REPAIRS • WIDE CRACKS
LOW SPOTS • DEPRESSIONS**

11.2 LBS.
www.super-seal.us



INSTRUCTIONS

Apply only if weather is dry & rain is not forecast for at least 24 hours. For ideal drying conditions, temperatures should be above 55° for at least 24 hours. Sweep area to be repaired. Scrub and clean any oil, gas spots and stains...rinse area with water. Scoop into area to be repaired, frequently dipping trowel in water. For fast dry results, apply in layers of 1/2" at a time. Each layer must dry before applying next (We do not recommend more than 2 layers). Level off, using a wet trowel. Feather edge of patch to surrounding surface. Drying time depends on temperature and weather conditions. For best overall results and appearance apply sealer to the repaired areas. Patch color may be brown when first applied, but it will turn black and blend in with surrounding asphalt pavement when fully cured. Applying too thick can result in shrinking and cracking. If shrinkage cracks appear, simply apply another thin coat.

NOTICE

These methods and techniques described herein represent some that have been used successfully to obtain the desired results. Allow patched pavement to fully cure. All variations in asphalt, climate conditions, and equipment cannot be anticipated by Dalton Enterprises. The decision to use any of these methods and techniques is entirely at the election and responsibility of the user.

EMERGENCY FIRST AID PROCEDURE:

Skin: wash exposed areas with soap and water.

Eyes: Flush with copious amounts of water, if symptoms persist, consult a physician.

Inhalation: Remove person to fresh air. If breathing is difficult administer oxygen. If breathing stops, give artificial respiration. Seek medical attention immediately.

Ingestion: Do not induce vomiting.

**DANGER - HARMFUL OR FATAL IF SWALLOWED
CALL PHYSICIAN IMMEDIATELY.**

SUPER SEAL™

SMOOTH PATCH

Shallow Asphalt Patch

- Black, Rubberized, Cement-Like Mix
- Asphaltic Adhesive, Self Bonding Formula
- Trowels To A Feather-Edge Finish

11.2 LBS.
www.super-seal.us

**SHALLOW REPAIRS • WIDE CRACKS
LOW SPOTS • DEPRESSIONS**

FOR DRIVEWAYS, WALKWAYS, PARKING LOTS
Ready-To-Use...Fast Dry Formula...Less Down Time



WARRANTY AND DISCLAIMER

There are no express warranties which extend beyond the description on the face hereof, MANUFACTURER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.

⚠ WARNING: This product can expose you to Crystalline Silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

CONTENTS/CAS#: Asphalt #8052-42-2; Water 7732-18-5; Clay 1332-58-7; Silica 14808-60-7
VOC <10g/l

**KEEP FROM FREEZING
KEEP OUT OF REACH OF CHILDREN**



SUPER SEAL® & SMOOTH PATCH® are trademarks of: Dalton Enterprises, Inc., 131 Willow Street Cheshire, CT 06410 USA 800-851-5606 www.super-seal.us Copyright © 2020

