

CLEAR

CLEAR



KWIK SEAL[®]
ULTRA[®]

ADVANCED SILICONIZED SEALANT

- 100% Waterproof & Crackproof
- 4 Hour Water Ready



EASY WATER CLEAN-UP & LOW ODOR

**Kitchen, Bath
& Plumbing**

Read back panel for cautions!
¡Lea las precauciones en el
panel posterior!

5.5 FL OZ (162 mL)

DAP[®] KWIK SEAL[®] ADVANCED KITCHEN & BATH SEALANT is formulated with innovative ultra-hydrophobic technology that repels water, dirt & stains & offers a lifetime mold & mildew resistance guarantee so the sealant stays looking clean, fresh & new. It is 100% waterproof & crackproof. Strong multi-surface adhesion & excellent flexibility for long lasting durability.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod.

Sealant applies white & dries clear in 7-14 days (depending on joint depth, temp & humidity). Sealant is not paintable. Paint surfaces before applying. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Remove cap & cut nozzle at 45° angle to desired bead size. 3. Squeeze sealant into gap or joint. 4. Smooth bead. 5. Clean up excess wet sealant with a damp sponge before it skins over. Clean hands & tools with warm water. Excess dried sealant must be cut or scraped away. 6. Wait 4 hours before exposing to water. Sealant reaches full performance in 24 hours. Regular cleaning of surrounding areas is suggested. 7. Reseal tube for storage & reuse.

COVERAGE: 30 linear ft at 3/16" diameter bead

CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses. **In an emergency,** call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

¡PRECAUCIÓN! Contiene etilenglicol. Utilice en un área bien ventilada. No permita el contacto con los ojos o la piel. No lo ingiere. Use guantes y gafas de seguridad. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Refiérase a la SDS para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer and Reproductive Harm / **ADVERTENCIA** Cáncer y Daños al Sistema Reproductor - www.P65warnings.ca.gov

NCCS Calif. ARB
<1.5 wt/wt% (VOC 28 g/L)



LIFETIME MOLD & MILDEW RESISTANCE GUARANTEE:

DAP warrants that this product will not mildew, crack, peel or separate when used as directed within one year of purchase. If product fails to perform when used as directed, within one year of date of purchase, call **888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

QUESTIONS? ¿PREGUNTAS? Call/Llame al **888-DAP-TIPS** or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al **888-327-8777** o visite dap.com.

©DAP Global Inc.,
Baltimore, MD 21224

Made in the USA with U.S. and globally sourced materials.

dap.com