




EASY TO USE acoustical putty

QuietPutty® is a moldable putty designed to maintain the performance of acoustically rated walls with penetrations such as electrical outlets, HVAC ducts, water hookups and cables.* QuietPutty® is clean, easy to use and requires no tools. Use as part of the Quiet® Sound Damping System for reliable, low cost results.



QuietPutty Benefits

- Adheres to most construction materials for a high quality seal
- Asbestos free
- Provides a draft and cold smoke seal
- Minimal shrinkage and will not dry out
- Noncorrosive to metal and plastics

Product Specifications:

Thickness: 1/8" (3mm) Width: 7" (178mm) Length: 7" (178mm) Weight: 7oz (198g) /pad Color: Blue/Green Unit Size: 10 pads/box

Surface Burn: (ASTM E84) Flame Spread 15,

Smoke developed: 250, Classification: A

Visit www.QuietRock.com for installation instructions and complete architectural documentation

The information contained in this document is for general purposes only. Construction practices have an influence on final STC ratings. PABCO® Gypsum cannot guarantee actual STC ratings. Flanking sound patterns, the integrity of the wall, and construction methods factor in effective sound control. QuietPutty® should be stored flat in a dry area to prevent damage to product.



^{*} Not recommended for use on penetrations with high temperature equipment or canned light canisters.