

AFR SLR-40 Specifications

C

ď

P

QuietCool

AIR SER-40 Specifications	
Airflow	1132 CFM (Airflow testing conducted to panel output at STC, AM1.5, 1000 W/m2, TC = 25° C)
HVI-916 Airflow (for CA)	950 CFM (Airflow testing conducted to panel output at STC, AM1.5, 1000 W/m2 , TC = 25°C)
Attic SQFT Coverage @ .75 CFM per SQFT	Covers up to 1,500 SQFT
Motor Voltage	DC
Inverter Energy Use	25.6 Watts
Inverter Voltage	120 VAC, 60 Hz
# of Fan Speeds	1
Housing Diameter	14.75"
Rough Cut-out Diameter	14"
Overall Height w/ Panel Up	19.5"
Overall Height w/ Panel Down	10.5"
Roof Cap Dimension	21.5" x 21.5"
Solar Panel Dimensions	19.5" x 19.5"
Flashing	23.5" x 23.5"
Primary Flashing (included)	For roofs 3:12 to 8:12 pitch
Curb Flashing - SLR-CRB-2424 (sold separately)	For flat roofs 3:12 pitch and below
Controls	Built-in Preset Thermostat (77 °F off 88 °F on)
Warranty	15 Years
Shipping Weight	47 lbs.
Box Dimensions	26" x 26" x 13.5"
In The Box	- AFR SLR-40
	- 20ft. AC/DC Inverter Cable

- Accessory Bag

Features & Benefits:

- 40 Watt Polycrystalline Solar Panel
- AC/DC Inverter for 24/7 cooling
- Save up to 30% on A/C related costs
- Plug and play (no wiring)
- Built-in Preset Thermostat



For more information, visit our website at: QUIETCOOLSYSTEMS.COM