



	Dimension	Weight	Order number
Installation Type: Alcove, Integrated acrylic panel front, White, Material: Sanitary acrylic, Number of backrests: 1 Right, Removable acces panel:, Includes support frame, Overflow: Yes, Drain orientation: Left, Overflow position: Foot end, Capacity gal: 53 gal, Internal Depth: 16 1/8 "			
Colors			
00 White			
Variant			
	60 40 4/0	74.957 lb	700654000000090
Seamless acrylic panel, ADA: Yes, cUPC listed: Yes	60 "x18 1/8 "	74.557 (8	
Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3	28 3/4 x 3 1/2 "	74.567 (2	792824
Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3 1/2 "		74.207 (2	
Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3 1/2 " Waste and overflow Bowden cable length: 21 ", 18 7/8 x 3/8 "	28 3/4 x 3 1/2 "	74.257 (2	792824
Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3 1/2 " Waste and overflow Bowden cable length: 21 ", 18 7/8 x 3/8 " Waste and overflow ADA: Yes, 42 1/2 x 3 1/2 "	28 3/4 x 3 1/2 " 18 7/8 x 3/8 "	74.257 (2	792824 792820
Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3 1/2 " Waste and overflow Bowden cable length: 21 ", 18 7/8 x 3/8 " Waste and overflow ADA: Yes, 42 1/2 x 3 1/2 " Waste and overflow ADA: Yes, 4 3/8 x 4 3/8 "	28 3/4 x 3 1/2 " 18 7/8 x 3/8 " 42 1/2 x 3 1/2 "	74.257 (2	792824 792820 792828
Seamless acrylic panel, ADA: Yes, cUPC listed: Yes Suitable products Waste and overflow Bowden cable length: 22 1/8 ", 28 3/4 x 3 1/2 " Waste and overflow Bowden cable length: 21 ", 18 7/8 x 3/8 " Waste and overflow ADA: Yes, 42 1/2 x 3 1/2 " Waste and overflow ADA: Yes, 4 3/8 x 4 3/8 " Mounting Bracket Mounting kit , 28 x 3 " Bolt Cap , 15 3/4 x 3 1/8 "	28 3/4 x 3 1/2 " 18 7/8 x 3/8 " 42 1/2 x 3 1/2 " 4 3/8 x 4 3/8 "	74.201 (2	792824 792820 792828 792829

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.