



SUPER SEAL®

Elastomeric Crack Filler

*High Performance
Blacktop Crack Filler*

- For cracks up to 1/2" wide
- Long lasting durable formula
- Expands & Contracts
- Fills up to 32 feet with 1/4" bead



10.1 FLUID OZ. CARTRIDGE

Warranty and Disclaimer: There are no express warranties which extend beyond the description on the face hereof. MANUFACTURER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will, at its option, either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.

SUPER SEAL®

Elastomeric Crack Filler

*High Performance
Blacktop Crack Filler*

USES

- To fill cracks in blacktop pavements
- Blacktop expansion Joints

DIRECTIONS

1. Clean cracks thoroughly.
2. Use for cracks up to 1/2" wide.
3. Apply when temperature is above 55°F & rain is not imminent for at least 24 hours.
4. Cracks over 1/2" deep should be filled with solid material to 3/8" from surface before caulking.
5. Cut nozzle at 45° angle to desired opening size & apply directly into crack using caulk gun.
6. Do not overfill.
7. Allow to fully cure prior to sealing.

KEEP OUT OF REACH OF CHILDREN

DO NOT TAKE INTERNALLY. IF SWALLOWED INDUCE VOMITING & CALL A PHYSICIAN: CONTAINS ACRYLIC LATEX

⚠ WARNING: This product can expose you to chemicals including Crystalline Silica and Carbon Black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Contents/Cas#:
Asphalt #8052-42-4; Crystalline Silica #14808-60-7;
Limestone #1317-65-3; Carbon Black #133-86-4;
Acrylic Emulsion Proprietary; Cellulose Fibers
#9004-34-6; Clay #1332-58-7
Max VOC 10g/L



Super Seal® is a trademark of:
Dalton Enterprises, Inc.,
Cheshire, CT 06410,
USA
Ph. 800-851-5606
www.super-seal.us
Copyright © 2020

