SAFETY DATA SHEET



1. Identification

Product identifier KILZ® Restoration Interior Primer

Other means of identification

Product code L2002

Recommended use **Architectural Coating**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Masterchem Industries LLC Supplier

> 3135 Old Highway M Imperial, MO 63052-2834

Telephone 636-942-2510 +1 760 476 3962 **Emergency telephone**

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Wash hands after handling. Response

Store away from incompatible materials. Storage

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Il name CAS number		
Kaolin, calcined	92704-41-1	10 - 30	
Titanium dioxide	13463-67-7	10 - 30	
Barium sulfate	7727-43-7	3 - 7	
Cristobalite	14464-46-1	0.1 - 1	
Diatomaceous Earth (Flux calcined)	68855-54-9	68855-54-9 0.1 - 1	

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

Communication Standard.

KILZ® Restoration Interior Primer

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Most important symptoms/effects, acute and

delayed

Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air Components	Contaminants (29 CFR 1910.7 Type	1000) Value	Form
Barium sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.

KILZ® Restoration Interior Primer SDS US

954881 Version #: 01 Revision date: -Issue date: 17-September-2020

Components	for Air Contaminants (29 CFR 1910. Type	Value	Form
		15 mg/m3	Total dust.
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF Components	R 1910.1000) Type	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Components	Values Type	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values	No biological exposure limits noted f	or the ingredient(s).	
propriate engineering trols	Good general ventilation should be use applicable, use process enclosures, maintain airborne levels below recornestablished, maintain airborne levels	local exhaust ventilation, or othen mended exposure limits. If exp	er engineering controls to
vidual protection measures Eye/face protection	such as personal protective equipm Wear safety glasses with side shield		
Skin protection Hand protection	Wear appropriate chemical resistant	gloves.	
Skin protection Other	Wear appropriate chemical resistant	clothing.	
Respiratory protection	If airborne concentrations are above respiratory protection. Use a positive uncontrolled release, exposure level air-purifying respirators may not pro-	the applicable exposure limits, uppressure air-supplied respirators are not known, or any other cit	r if there is any potential fo

KILZ® Restoration Interior Primer SDS US

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color White.
Odor Slight.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not Applicable.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(a/)

Not Applicable.

(%)

Flammability limit - upper

Not Applicable.

Not available.

(%)

Vapor pressureNot available.Vapor densityNot available.

Relative density 1.37

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Viscosity 50 - 140 KU at 25°C

Other information

Decomposition temperature

Density11.45 lbs/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 32 g/l (including water)(Material) 76 g/l (excluding water)(Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

KILZ® Restoration Interior Primer

954881 Version #: 01 Revision date: - Issue date: 17-September-2020

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Barium sulfate (CAS 7727-43-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

CarcinogenicityDue to the form of the product, exposure to the potentially carcinogenic components is not

expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1) Cancer Diatomaceous Earth (Flux calcined) (CAS 68855-54-9) Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potentialNo data available.Mobility in soilNo data available.Other adverse effectsNo data available.

13. Disposal considerations

KILZ® Restoration Interior Primer

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium sulfate (CAS 7727-43-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1) Cancer Diatomaceous Earth (Flux calcined) Cancer

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) lung effects Diatomaceous Earth (Flux calcined) lung effects

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) immune system effects Diatomaceous Earth (Flux calcined) immune system effects

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) kidney effects Diatomaceous Earth (Flux calcined) kidney effects

(CAS 68855-54-9)

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

KILZ® Restoration Interior Primer SDS US

US state regulations

US. Massachusetts RTK - Substance List

Barium sulfate (CAS 7727-43-7) Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Barium sulfate (CAS 7727-43-7) Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Barium sulfate (CAS 7727-43-7) Cristobalite (CAS 14464-46-1)

Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Barium sulfate (CAS 7727-43-7) Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 17-September-2020

Revision date - 01

HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Masterchem Industries LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

KILZ® Restoration Interior Primer SDS US