

Sunward®

5.5' Bath **K-6346**



Features

- Under-mount
- Integral lumbar support and armrests for comfort.
- End drain

Material

Acrylic

Installation

Drop-in or under-mount.

Recommended Accessories

K-24916 Wireless Music Kit K-738 Under-Mount Install Kit - K-6346/K-6347



Codes/Standards

CSA B45.5/IAPMO Z124 Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond






Sunward®


5.5' Bath K-6346

No change in measurements if connected with drain illustrated. (K-37382)

Recommended Faucet Location







Technical Information


All product dimensions are nominal.

Installation: Drop-in End Drain location:

48-5/8" x 24-1/2" (1235 mm x 622 mm) Basin area, bottom: 60" x 32-3/16" (1523 mm x 818 mm) Basin area, top:

Minimum floor load: 34 lbs/ft² (166 kg/m²) Water depth: 14-5/16" (364 mm) Water capacity: 70 gal (265 L)

Template: Drop-in, 1233384-7, not required, included



Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Kit is required for under-mount installations (sold separately).

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

