


Design & Size Options

LIVINGSTON.		PASSAGE														BIFOLDS							
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	24"	28"	30"	32"	36"	48"	60"	72"
	LIVINGSTON.. (3 PANEL)																						
	Livingston 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Livingston 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Livingston 96"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
HERITAGE SERIES.		PASSAGE														BIFOLDS							
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	24"	28"	30"	32"	36"	48"	60"	72"
	LINCOLN PARK.. (1 PANEL)																						
	Craftsman 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	LOGAN.. (2 PANELS)																						
	Craftsman 80"	•*▲	•▲	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•▲	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	WINSLOW.. (3 PANELS)																						
	Craftsman 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Craftsman 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WEST END COLLECTION.		PASSAGE														BIFOLDS							
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	24"	28"	30"	32"	36"	48"	60"	72"
	MELROSE																						
	Embossed Groove 80"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Embossed Groove 84"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	BERKLEY.																						
	Embossed Groove 80"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Embossed Groove 84"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
MOLDED PANEL SERIES		PASSAGE														BIFOLDS							
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	24"	28"	30"	32"	36"	48"	60"	72"
	CHEYENNE.																						
	Cheyenne 80"	•*▲	•*▲	•▲	•	•*▲	•	•*▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Cheyenne 96"	•*▲	•*▲	•▲	•	•*▲	•	•*▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	RIVERSIDE.																						
	Riverside 80"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Riverside 84"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Riverside 96"	•*▲	•	•	•	•	•	•▲	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.


Design & Size Options

MOLDED PANEL SERIES		PASSAGE															BIFOLDS								
		12"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	24"	28"	30"	32"	36"	48"	60"	72"	
	2 PANEL ARCH-TOP																								
	Textured C&B 80"	•*▲	•▲	•▲	•	•	•	•▲	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	
	2 PANEL ROMAN																								
	Smooth INP 80"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 84"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 96"					•*▲	•▲	•*▲	•	•	•	•	•	•	•				•	•	•		•	•	
	2 PANEL																								
	Smooth INP 80"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 84"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 96"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	4 PANEL																								
	Smooth INP 80"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 84"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 96"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	6 PANEL																								
	Smooth INP 80"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 84"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Smooth INP 96"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Textured C&B 80"	•*▲	•▲	•▲	•	•*▲	•▲	•*▲	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	Textured C&B 84"								•	•	•	•	•	•	•		•	•	•	•	•		•	•	•
	2 PANEL COMMERCIAL																								
	Smooth INP 80"											•	•	•	•										
	Smooth INP 84"											•	•	•	•										

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options


LIVINGSTON.	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
LIVINGSTON. (3 PANEL)												
	12" 14" 15" 16"	80" 84" 96"	3	1-3/8" 1-3/4"	6.5"	2.75 (12")* [▲] 3.75 (14") 4.25 (15") 4.75 (16")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	18" 20"	80" 84" 96"	3	1-3/8" 1-3/4"	8.50"	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	22" 24" 26"	80" 84" 96"	3	1-3/8" 1-3/4"	14.5"	3.75 (22")* [▲] 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	28"	80" 84" 96"	3	1-3/8" 1-3/4"	18.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	30"	80" 84" 96"	3	1-3/8" 1-3/4"	20.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	32" 34"	80" 84" 96"	3	1-3/8" 1-3/4"	22.50"	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth
	36"	80" 84" 96"	3	1-3/8" 1-3/4"	26.50"	4.75	N/A	4.25 (80") 6.25 (84") 4.50 (96")	N/A	10.875 (80") 12.875 (84") 10.875 (96")	Liv	Smooth


LIVINGSTON. BIFOLD	WIDTH NOMINAL	HEIGHT NOMINAL	WIDTH ACTUAL	HEIGHT ACTUAL	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER STILES	TOP RAIL	LOCK RAIL	BOTTOM RAIL
LIVINGSTON. (3 PANEL)												
	24"	80" 84" 96"	23.5"	79" 83" 95"	6	1-3/8"	5.375	4.625	1.75	4.25 (80") 6.25 (84") 4.25 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	28"	80" 84" 96"	27.5"	79" 83" 95"	6	1-3/8"	8.375	3.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	30"	80" 84" 96"	29.5"	79" 83" 95"	6	1-3/8"	8.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	32"	80" 84" 96"	31.5"	79" 83" 95"	6	1-3/8"	11.375	2.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	36"	80" 84" 96"	35.5"	79" 83" 95"	6	1-3/8"	11.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	48"	80" 84" 96"	47.5"	79" 83" 95"	12	1-3/8"	5.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	60"	80" 84" 96"	59.5"	79" 83" 95"	12	1-3/8"	8.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")
	72"	80" 84" 96"	71.5"	79" 83" 95"	12	1-3/8"	11.375	4.625	1.75	4.25 (80") 6.25 (84") 4.50 (96")	N/A	9.875 (80") 11.875 (84") 9.875 (96")


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options

HERITAGE SERIES.		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
LINCOLN PARK.. (1 PANEL)													
	12" 14" 15" 16"	80" 84" 84" 96"	1	1-3/8" 1-3/4"	5.75	3.12 (12")*^ 4.12 (14") 4.62 (15") 5.12 (16")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	18" 20"	80" 84" 96"	1	1-3/8" 1-3/4"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	22" 24" 26"	80" 84" 96"	1	1-3/8" 1-3/4"	14.5	3.75 (22")*^ 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	28"	80" 84" 96"	1	1-3/8" 1-3/4"	18.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	30"	80" 84" 96"	1	1-3/8" 1-3/4"	20.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	32" 34"	80" 84" 96"	1	1-3/8" 1-3/4"	22.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	36"	80" 84" 96"	1	1-3/8" 1-3/4"	24.5	5.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	

HERITAGE SERIES.		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
LOGAN.. (2 PANELS)													
	12" 14" 15" 16"	80" 84" 84" 96"	2	1-3/8" 1-3/4"	6.5	2.75 (12")*^ 3.75 (14")^ 4.25 (15") 4.75 (16")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	18" 20"	80" 84" 96"	2	1-3/8" 1-3/4"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	22" 24" 26"	80" 84" 96"	2	1-3/8" 1-3/4"	14.5	3.75 (22")^ 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	28"	80" 84" 96"	2	1-3/8" 1-3/4"	18.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	30"	80" 84" 96"	2	1-3/8" 1-3/4"	20.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	32" 34"	80" 84" 96"	2	1-3/8" 1-3/4"	22.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	
	36"	80" 84" 96"	2	1-3/8" 1-3/4"	24.5	5.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	6.75	10.87 (80") 12.87 (84") 10.87 (96")	C	Smooth	

HERITAGE SERIES.		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
WINSLOW- (3 PANELS)													
	12"	80"	2	1-3/8"	5.75	3.125 (12")*	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth	
	14"					4.125 (14")							
	15"					4.625 (15")							
	16"					5.125 (16")							
	18"	80"	2	1-3/8"	8.5	4.75 (18")	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth	
	20"	5.75 (20")											
	22"	80"	3	1-3/8"	14.5	3.75 (22")*	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth	
	24"	84"				4.75 (24")							
	26"	80"	3	1-3/8"	16.5	5.75 (26")	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth	
	28"	84"				4.75 (28")							
30"	80"	3	1-3/8"	20.5	4.75 (32")	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth		
32"	84"				5.75 (34")								
34"	80"	3	1-3/8"	24.5	4.75 (34")	N/A	4.25 (80")	N/A	10.87 (80")	C	Smooth		
36"	84"				5.75 (36")								

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options


WEST END COLLECTION. MELROSE.	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
	12" - 36"	80" 84"	6	1-3/8" 1-3/4"	12" - 36"	N/A	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth


WEST END COLLECTION. BERKLEY.	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
	12"	80" 84"	6	1-3/8" 1-3/4"	7.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	14"	80" 84"	6	1-3/8" 1-3/4"	9.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	15"	80" 84"	6	1-3/8" 1-3/4"	10.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	16"	80" 84"	6	1-3/8" 1-3/4"	11.67	4.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	18"	80" 84"	6	1-3/8" 1-3/4"	11.67	6.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	20"	80" 84"	6	1-3/8" 1-3/4"	13.67	6.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	22"	80" 84"	6	1-3/8" 1-3/4"	13.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	24"	80" 84"	6	1-3/8" 1-3/4"	15.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	26"	80" 84"	6	1-3/8" 1-3/4"	17.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	28"	80" 84"	6	1-3/8" 1-3/4"	18.67	9.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	30"	80" 84"	6	1-3/8" 1-3/4"	21.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	32"	80" 84"	6	1-3/8" 1-3/4"	23.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	34"	80" 84"	6	1-3/8" 1-3/4"	25.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth
	36"	80" 84"	6	1-3/8" 1-3/4"	27.67	8.18	N/A	13 (80") 15 (84")	N/A	13 (80") 15 (84")	N/A	Smooth

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options


MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
CHEYENNE													
	12"	80" 96"	2	1-3/8" 1-3/4"	7.5	2.25 (12")** 3.25 (14")** 3.75 (15") * 4.25 (16")	N/A	4.25 (80") 4.25 (96")	7	8.37 (80") 8.37 (96")	Chey	Smooth	
	14"												
	15"												
	16"												
	18"	80" 96"	2	1-3/8" 1-3/4"	11.67	3.16 (18")** 4.16 (20")	N/A	4.25 (80") 4.25 (96")	7	8.37 (80") 8.37 (96")	Chey	Smooth	
	20"												
	22"	80" 96"	2	1-3/8" 1-3/4"	15.75	3.12 (22")** 4.12 (24") 5.12 (26")	N/A	4.25 (80") 4.25 (96")	7	8.37 (80") 8.37 (96")	Chey	Smooth	
	24"												
	26"												
28"	80" 96"	2	1-3/8" 1-3/4"	19.75	4.12	N/A	4.25 (80") 4.25 (96")	7	8.37 (80") 8.37 (96")	Chey	Smooth		
30"													
32"	80" 96"	2	1-3/8" 1-3/4"	23.75	4.12 (32") 5.12 (34")	N/A	4.25 (80") 4.25 (96")	7	8.37 (80") 8.37 (96")	Chey	Smooth		
34"													
36"													


MOLDED PANEL SERIES		WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
RIVERSIDE													
	12"	80" 84" 96"	5 (80", 84") 6 (96")	1-3/8" 1-3/4"	5.75	3.12 (12")** 4.12 (14") 4.62 (15") 5.12 (16")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	8.38 (80") 10.38 (84") 8.38 (96")	Riv	Smooth	
	14"												
	15"												
	16"												
	18"	80" 84" 96"	5 (80", 84") 6 (96")	1-3/8" 1-3/4"	8.5	4.75 (18") 5.75 (20")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	8.38 (80") 10.38 (84") 8.38 (96")	Riv	Smooth	
	20"												
	22"	80" 84" 96"	5 (80", 84") 6 (96")	1-3/8" 1-3/4"	14.5	3.75 (22")* 4.75 (24") 5.75 (26")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	8.38 (80") 10.38 (84") 8.38 (96")	Riv	Smooth	
	24"												
	26"												
28"	80" 84" 96"	5 (80", 84") 6 (96")	1-3/8" 1-3/4"	18.5	4.75	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	8.38 (80") 10.38 (84") 8.38 (96")	Riv	Smooth		
30"													
32"	80" 84" 96"	5 (80", 84") 6 (96")	1-3/8" 1-3/4"	22.5	4.75 (32") 5.75 (34")	N/A	4.25 (80") 6.25 (84") 4.25 (96")	N/A	8.38 (80") 10.38 (84") 8.38 (96")	Riv	Smooth		
34"													
36"													


* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options

MOLDED PANEL SERIES	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL ARCH-TOP (TEXTURED)												
	12" 14" 15" 16"	80"	2	1-3/8" 1-3/4"	7	2.5 (12") ⁺ 3.5 (14") ⁺ 4.0 (15") ⁺ 4.5 (16")	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	18" 20"	80"	2	1-3/8" 1-3/4"	9.5	4.25 (18") 5.25 (20")	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	22" 24" 26"	80"	2	1-3/8" 1-3/4"	14.96	3.52 (22") ⁺ 4.52 (24") 5.52 (26")	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	28"	80"	2	1-3/8" 1-3/4"	18.1	4.95	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	30"	80"	2	1-3/8" 1-3/4"	19.69	5.15	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	32" 34"	80"	2	1-3/8" 1-3/4"	22.85	4.57 (32") 5.57 (34")	N/A	4.75 (80")	3.74	8.51	C&B	Textured
	36"	80"	2	1-3/8" 1-3/4"	25	5.5	N/A	4.75 (80")	3.74	8.51	C&B	Textured




MOLDED PANEL SERIES	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL ROMAN												
	12" 14" 15" 16"	80" 84"	2	1-3/8" 1-3/4"	7.08	2.45 (12") ⁺ 3.45 (14") ⁺ 3.95 (15") ⁺ 4.45 (16")	N/A	4.75 (80") 6.75 (84")	6.78	8.25 (80") 10.25 (84")	INP	Smooth
	18" 20"	80" 84" 96"	2	1-3/8" 1-3/4"	11.96	3 (18") ⁺ 4 (20") ⁺	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	22" 24" 26"	80" 84" 96"	2	1-3/8" 1-3/4"	15.69	3.15 (22") ⁺ 4.15 (24") 5.15 (26")	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	28"	80" 84" 96"	2	1-3/8" 1-3/4"	17.69	5.15	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	30"	80" 84" 96"	2	1-3/8" 1-3/4"	19.69	5.15	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	32" 34"	80" 84" 96"	2	1-3/8" 1-3/4"	21.69	5.15 (32") 6.15 (34")	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	36"	80" 84" 96"	2	1-3/8" 1-3/4"	23.69	6.15	N/A	4.75 (80") 6.75 (84") 6.75 (96")	6.78	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth

MOLDED PANEL SERIES	WIDTH	HEIGHT	# OF PANELS	THICKNESS	PANEL WIDTH	OUTER STILES	CENTER MULLION	TOP RAIL	LOCK RAIL	BOTTOM RAIL	STICKING PROFILE	SURFACE
2 PANEL												
	12" 14" 15" 16"	80" 84" 96"	2	1-3/8" 1-3/4"	7.08	2.45 (12") ⁺ 3.45 (14") ⁺ 3.95 (15") ⁺ 4.45 (16")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	18" 20"	80" 84" 96"	2	1-3/8" 1-3/4"	11.96	3 (18") ⁺ 4 (20") ⁺	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	22" 24" 26"	80" 84" 96"	2	1-3/8" 1-3/4"	15.69	3.15 (22") ⁺ 4.15 (24") 5.15 (26")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	28"	80" 84" 96"	2	1-3/8" 1-3/4"	17.69	5.15	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	30"	80" 84" 96"	2	1-3/8" 1-3/4"	19.69	5.15	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	32" 34"	80" 84" 96"	2	1-3/8" 1-3/4"	21.69	5.15 (32") 6.15 (34")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	36"	80" 84" 96"	2	1-3/8" 1-3/4"	23.69	6.15	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.8	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.


Design & Size Options


MOLDED PANEL SERIES												
4 PANEL												
	12" 14" 15" 16"	80" 84" 96"	2	1-3/8" 1-3/4"	7.08	2.45 (12") [▲] 3.45 (14") [▲] 3.95 (15") [▲] 4.45 (16")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	18" 20"	80" 84" 96"	2	1-3/8" 1-3/4"	11.96	3 (18") [▲] 4 (20") [▲]	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	22" 24" 26"	80" 84" 96"	4	1-3/8" 1-3/4"	5.96	3.15 (22") [▲] 4.15 (24") 5.15 (26")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	28"	80" 84" 96"	4	1-3/8" 1-3/4"	7.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	30"	80" 84" 96"	4	1-3/8" 1-3/4"	8.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	32" 34"	80" 84" 96"	4	1-3/8" 1-3/4"	9.96	4.15 (32") 5.15 (34")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	36"	80" 84" 96"	4	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.78"	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
MOLDED PANEL SERIES												
6 PANEL (SMOOTH)												
	12" 14" 15" 16"	80" 84" 96"	3	1-3/8" 1-3/4"	7.08	2.45 (12") [▲] 3.45 (14") [▲] 3.95 (15") [▲] 4.45 (16")	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	18" 20"	80" 84" 96"	3	1-3/8" 1-3/4"	11.96	3 (18") [▲] 4 (20") [▲]	N/A	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	22" 24" 26"	80" 84" 96"	6	1-3/8" 1-3/4"	5.96	3.15 (22") [▲] 4.15 (24") 5.15 (26")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	28"	80" 84" 96"	6	1-3/8" 1-3/4"	7.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	30"	80" 84" 96"	6	1-3/8" 1-3/4"	8.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	32" 34"	80" 84" 96"	6	1-3/8" 1-3/4"	9.96	4.15 (32") 5.15 (34")	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
	36"	80" 84" 96"	6	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25 (80") 6.25 (84") 5.25 (96")	6.77	8.25 (80") 10.25 (84") 8.25 (96")	INP	Smooth
MOLDED PANEL SERIES												
6 PANEL (TEXTURED)												
 PRIMED & WHITE	12" 14" 15" 16"	80"	3	1-3/8" 1-3/4"	7.08	2.45 (12") [▲] 3.45 (14") [▲] 3.95 (15") [▲] 4.45 (16")	N/A	4.28	6.81	8.28	C&B	Textured
	18" 20"	80"	3	1-3/8" 1-3/4"	11.96	3 (18") [▲] 4 (20") [▲]	N/A	4.28	6.81	8.28	C&B	Textured
	22" 24" 26"	80" 84" 96"	6	1-3/8" 1-3/4"	5.94	3.15 (22") [▲] 4.15 (24") 5.15 (26")	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured
	28"	80" 84" 96"	6	1-3/8" 1-3/4"	7.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured
	30"	80" 84" 96"	6	1-3/8" 1-3/4"	8.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured
	32" 34"	80" 84" 96"	6	1-3/8" 1-3/4"	9.94	4.15 (32") 5.15 (34")	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured
	36"	80" 84" 96"	6	1-3/8" 1-3/4"	11.94	4.15	3.81	4.28 (80") 6.28 (84") 5.28 (96")	6.81	8.28 (80") 10.28 (84") 8.28 (96")	C&B	Textured

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

Design & Size Options

MOLDED PANEL SERIES												
6 PANEL (TEXTURED)												
 PRESTAINED	12" 14" 15" 16"	80"	3	1-3/8" 1-3/4"	7.08	2.46 (12") [▲] 3.46 (14") [▲] 3.96 (15") [▲] 4.46 (16")	N/A	4.25	6.77	8.25	INP	Textured
	18" 20"					3.02 (18") [▲] 4.02 (20") [▲]						
	22" 24" 26"	80"	6	1-3/8" 1-3/4"	5.96	3.15 (22") [▲] 4.15 (24") 5.15 (26")	3.78	4.25	6.77	8.25	INP	Textured
	28"					4.15						
	30"	80"	6	1-3/8" 1-3/4"	8.96	4.15	3.78	4.25	6.77	8.25	INP	Textured
	32" 34"					4.15 (32") 5.15 (34")						
	36"	80"	6	1-3/8" 1-3/4"	11.96	4.15	3.78	4.25	6.77	8.25	INP	Textured

MOLDED PANEL SERIES												
2 PANEL COMMERCIAL												
	30" 32"	80" 84"	2	1-3/8" 1-3/4"	19.69	5.15 (30") 6.15 (32")	N/A	4.75 (80") 6.75 (84")	6.78	10.87 (80") 12.87 (84")	INP	Smooth
	34" 36"	80" 84"				5.5 (34") 6.5 (36")		4.75 (80") 6.7 (84")		10.87 (80") 12.87 (84")		

* Standard bore machining (2-1/8" diameter) requires a stile no less than **3.6875"** to accommodate a **2-3/8" backset**.

▲ Standard bore machining (2-1/8" diameter) requires a stile no less than **4.0625"** to accommodate a **2-3/4" backset**.

⚠ WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.