Printing date 24.06.2014

Revision: 24.06.2014

· 1.1 Product ide		
	fing Solution (Rubber Cleaner)	
	14-100 ntified uses of the substance or mixture and uses advised against t information available.	
· Application of t	e substance / the mixture Cleaner solvent	
Manufacturer/S 31 Incorporated 100 Enterprise D Newcomerstown Phone: (740) 498	OH 43832 -8324 elephone number:	
2 Hazards iden	ification	
· Classification a	n of the substance or mixture cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec	ific CLF
Classification a The following cla regulation: H361	cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec azard Statements are applicable only to the EU regulations and not the L	
• Classification a The following cla regulation: H361 The following H regulation: H361	cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec azard Statements are applicable only to the EU regulations and not the L	
• Classification a The following cla regulation: H361 The following H regulation: H361	cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec azard Statements are applicable only to the EU regulations and not the U H400, H410.	
Classification a The following cla regulation: H361 The following H regulation: H361 flame Flam. Liq. 2	cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec azard Statements are applicable only to the EU regulations and not the U H400, H410.	
Classification a The following cla regulation: H361 The following H regulation: H361 following H regulation: H361 following H regulation: H361 following H regulation: H361 following H regulation: H361 health ha	 cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spectazard Statements are applicable only to the EU regulations and not the L H400, H410. H225 Highly flammable liquid and vapour. rard H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure 	S GH
Classification a The following cla regulation: H361 The following H regulation: H361 flame Flam. Liq. 2 Repr. 2	cording to Regulation (EC) No 1272/2008 sifications are applicable only to the general GHS regulations and not the spec azard Statements are applicable only to the EU regulations and not the U H400, H410. H225 Highly flammable liquid and vapour. zard H361f Suspected of damaging fertility.	S GH
Classification a The following cla regulation: H361 The following H regulation: H361 following H regulation: H361 flame Flam. Liq. 2 flame Repr. 2 STOT RE 2	 cording to Regulation (EC) No 1272/2008 asifications are applicable only to the general GHS regulations and not the spectazard Statements are applicable only to the EU regulations and not the U H400, H410. H225 Highly flammable liquid and vapour. card H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 	S GH
Classification a The following cla regulation: H361 The following H regulation: H361 following H regulation: H361 flame Flam. Liq. 2 flame Flam. Liq. 2 STOT RE 2 Asp. Tox. 1	 cording to Regulation (EC) No 1272/2008 asifications are applicable only to the general GHS regulations and not the spectazard Statements are applicable only to the EU regulations and not the U H400, H410. H225 Highly flammable liquid and vapour. card H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 	S GH
Classification a The following cla regulation: H361 The following H regulation: H361 following H regulation: H361 flame Flam. Liq. 2 flame Flam. Liq. 2 flame health ha Repr. 2 STOT RE 2 Asp. Tox. 1 Aquatic Acute 1	 cording to Regulation (EC) No 1272/2008 asifications are applicable only to the general GHS regulations and not the spectazard Statements are applicable only to the EU regulations and not the L H400, H410. H225 Highly flammable liquid and vapour. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 	S GH

Printing date 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

Revision: 24.06.2014

	(Contri of page 1)
Eye Irrit. 2	(Contd. of page 1) (Contd. of page 1)
STOT SE 3	H336 May cause drowsiness or dizziness.
· Classification a	according to Directive 67/548/EEC or Directive 1999/45/EC
🗙 Xn; Harmful	
R48/20-62-65:	Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed.
🗙 Xi; Irritant	
R36/38:	Irritating to eyes and skin.
F; Highly fla	mmable
R11:	Highly flammable.
N; Dangero	us for the environment
R50/53:	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
The product has for preparations • Classification s The classificati literature data. The classificati supplemented b • 2.2 Label eleme • Labelling acco The product is c	on is according to the latest editions of the EU-lists, and extended by company and on is in accordance with the latest editions of international substances lists, and is y information from technical literature and by information provided by the company. ents rding to Regulation (EC) No 1272/2008 lassified and labelled according to the CLP regulation. ams etogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).
· Signal word Da	inger
 Hazard-determ n-hexane heptane acetone 	ining components of labelling:
	(Contd. on page 3)

GHS

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner) (Contd. of page 2) · Hazard statements The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f, H410. The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361. H361: Suspected of damaging fertility or the unborn child. H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H361f Suspected of damaging fertility. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210 P281 Use personal protective equipment as required. P233 Keep container tightly closed. P264 Wash thoroughly after handling. P260 Do not breathe mist/vapours/spray. P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction. Get medical advice/attention if you feel unwell. P314 P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Hazard description: · WHMIS-symbols: B2 - Flammable liquid D2A - Very toxic material causing other toxic effects • NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH *2 Health = *2 ³ Fire = 3 FIRE Reactivity = 0 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 110-54-3 n-hexane (Contd. on page 4)

Printing date 24.06.2014

Revision: 24.06.2014

(Contd. of page 3)

Trade name: Buffing Solution (Rubber Cleaner)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Xn R48/20-62-65; Xi R38; F R11; N R51/53 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Xn R65; Xi R38; F R11; N R50/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	 ♦ Flam. Liq. 2, H225 ♦ Eye Irrit. 2, H319; STOT SE 3, H336 	20-40%
 Additional information: For 	the wording of the listed risk phrases refer to section 16.	

4 First aid measures

· 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 5)

GHS

Printing date 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

Revision: 24.06.2014

	(Contd. of page
 After skin contact: 	
Immediately remove any clothing so	
Immediately wash with water and s	
If skin irritation continues, consult a	doctor.
After eye contact:	
Remove contact lenses if worn.	
Rinse opened eye for several minut	tes under running water. If symptoms persist, consult a doctor.
· After swallowing:	
Rinse out mouth and then drink ple	
Do not induce vomiting; call for med	
A person vomiting while laying on the	heir back should be turned onto their side.
· 4.2 Most important symptoms an	d effects, both acute and delayed
Breathing difficulty	•
Dizziness	
Headache	
Coughing	
Irritant to skin and mucous membra	ines.
Irritant to eyes.	
Gastric or intestinal disorders when	ingested.
Nausea	-
Disorientation	
Hazards	
Danger of pulmonary oedema.	
Danger of pneumonia.	
Danger of impaired breathing.	
May be harmful in contact with skin	
May be harmful if inhaled.	
Repeated exposure may cause skir	n dryness or cracking.
Vapours may cause drowsiness an	
Suspected of damaging fertility or th	
Danger of disturbed cardiac rhythm	
Danger of convulsion.	
Possible risk of irreversible effects.	
4.3 Indication of any immediate n	nedical attention and special treatment needed
If swallowed, gastric irrigation with a	
If necessary oxygen respiration trea	
If swallowed or in case of vomiting,	
Later observation for pneumonia ar	
Vapours may cause drowsiness an	
Medical supervision for at least 48 l	

5 Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

• For safety reasons unsuitable extinguishing agents: Water

(Contd. on page 6)

GHS

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 5)

• **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.

• 5.3 Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Allow to evaporate.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Rags, metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed metal container rated for flammable waste.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may form in empty receptacles.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 7)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 6) · 7.2 Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Store in a cool location. Provide ventilation for receptacles. Avoid storage near extreme heat, ignition sources or open flame. · Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents. · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed. · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

· Ingredients v	vith limit values that require monitoring at the workplace:
110-54-3 n-he	exane
IOELV (EU)	Long-term value: 72 mg/m ³ , 20 ppm
PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm
142-82-5 hep	tane
IOELV (EU)	Long-term value: 2085 mg/m ³ , 500 ppm
PEL (USA)	Long-term value: 2000 mg/m³, 500 ppm
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit: 1800* mg/m³, 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m³, 500 ppm Long-term value: 1,635 mg/m³, 400 ppm
	(Contd. on page 8)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

07.04.4		(Contd. of page 7)
67-64-1 acet		
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm	
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm BEI	
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm	
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm	
• PNECs No fu	rther relevant information available. rther relevant information available.	
 Ingredients 	vith biological limit values:	
110-54-3 n-h	exane	
T	edium: urine me: end of shift at end of workweek arameter: 2,5-Hexanedione without hydrolysis	
67-64-1 acet	one	
T) mg/L edium: urine me: end of shift arameter: Acetone (nonspecific)	
	formation: The lists valid during the making were used as basis.	
General prot The usual prot Pregnant wor Keep away fr Immediately r Wash hands Do not inhale Avoid contact Respiratory Not required Use suitable Use suitable For spills, res	tective equipment: ective and hygienic measures: cautionary measures are to be adhered to when handling chemicals. nen should strictly avoid inhalation or skin contact. om foodstuffs, beverages and feed. emove all soiled and contaminated clothing. before breaks and at the end of work. gases / fumes / aerosols. with the eyes and skin.	d be used. (Contd. on page 9)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 8)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Solvent resistant protective clothing
- Limitation and supervision of exposure into the environment No further relevant information available.
- Risk management measures See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information	
· Appearance:	
Form:	Liquid
Colour:	White
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not Determined. 180 ° F / 82 °C
· Flash point:	5 ° F / -15 °C
· Flammability (solid, gaseous):	Not applicable.
· Auto/Self-ignition temperature:	419 ° F / 215 °C

(Contd. on page 10)

GHS

Printing date 24.06.2014

Revision: 24.06.2014

rade name: Buffing Solution (Rubbe	r Cleaner)
	(Contd. of page 9)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
 Explosion limits: Lower: Upper: 	1,1 Vol % 13,0 Vol %
· Vapour pressure at 20 °C:	233 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0,76 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	iter): Not determined.
 Viscosity: Dynamic: Kinematic: 9.2 Other information 	Not determined. Not determined. No further relevant information available.

10 Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.

10.3 Possibility of hazardous reactions

Flammable.

Reacts violently with oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised. Toxic fumes may be released if heated above the decomposition point.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 11)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 10)

	ogical information		
· 11.1 Info · Acute to	rmation on toxicological effects xicity:		
	· LD/LC50 values relevant for classification:		
142-82-5			
Oral	LD50 > 5000 mg/kg (rat) (Estimate)		
	LC50/4h 103 mg/l (rat)		
	rritant effect: sin: Irritant to skin and mucous membranes.		
	re: Irritating effect.		
	ition: No sensitizing effects known.		
	al toxicological information:		
The proc	luct shows the following dangers according to the calculation method of the General E tion Guidelines for Preparations as issued in the latest version:		
Inhalatio headach	n of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions an e, dizziness, etc.		
	l/or corrosive effects may be delayed up to 12 hours.		
	d of damaging fertility or the unborn child. Tects (acute toxicity, irritation and corrosivity):		
	nave narcotic effect.		
	armful if swallowed.		
	armful in contact with skin.		
	armful if inhaled.		
	dose toxicity:		
	e damage to organs through prolonged or repeated exposure. I exposure may cause skin dryness or cracking.		
	ects (carcinogenity, mutagenicity and toxicity for reproduction):		
Repr. 2	ets (careinogenity, matagementy and toxicity for reproduction).		
2 Ecolog	ical information		
· 12.1 Tox	city		
	oxicity: Toxic for aquatic organisms		
	sistence and degradability Easily biodegradable		
	accumulative potential No further relevant information available.		
	ility in soil No further relevant information available.		
· 12.4 Mot			
· Ecotoxic	al effects:		
 Ecotoxic Remark: 			
 Ecotoxic Remark: Very toxi 	c for fish		
 Ecotoxic Remark: Very toxi The prod 			

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 12)

GHS

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 11)

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · 14.1 UN-Number
- \cdot DOT, ADR, IMDG, IATA
- · 14.2 UN proper shipping name
- · DOT
- · ADR
- · IMDG, IATA
- · 14.3 Transport hazard class(es)
- · DOT



UN1993

Flammable liquids, n.o.s. (hexanes, heptanes) 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES, HEPTANES), ENVIRONMENTALLY HAZARDOUS FLAMMABLE LIQUID, N.O.S. (HEXANES, HEPTANES)

3 Flammable liquids.

(Contd. on page 13)

Printing date 24.06.2014

Revision: 24.06.2014

ade name: Buffing Solution (Rubber (Cleaner)
· Label	(Contd. of page 1
ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
Label	3
 14.4 Packing group 	
DOT, ADR, IMDG, IATA	II
• 14.5 Environmental hazards:	NI-
• Marine pollutant:	No Symbol (fich and trac)
 Special marking (ADR): 14.6 Special precautions for user 	Symbol (fish and tree) Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-E
• 14.7 Transport in bulk according to	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
 Limited quantities (LQ) 	1L
· Transport category	2
Tunnel restriction code	D/E
UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (HEXANE HEPTANES), ENVIRONMENTALLY HAZARDOUS, II

15 Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot United States (USA)

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

(Contd. on page 14)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

TSCA (Toxic Substances Control Act):	(Contd. of page
All ingredients are listed.	
Proposition 65 (California):	
• Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic Categories	
EPA (Environmental Protection Agency)	
110-54-3 n-hexane	
142-82-5 heptane	
67-64-1 acetone	
IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
• TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	ŀ
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
Canada	
Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 1%)	
All ingredients are listed.	
• Other regulations, limitations and prohibitive regulations This product has been classified in accordance with hazard criteria Regulations and the SDS contains all the information required by the Contro	
Substances of very high concern (SVHC) according to REACH, Article	-
None of the ingredients is listed.	
• 15.2 Chemical safety assessment: A Chemical Safety Assessment has no	ot been carried out.

(Contd. on page 15)

Printing date 24.06.2014

Revision: 24.06.2014

Trade name: Buffing Solution (Rubber Cleaner)

(Contd. of page 14)

16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases Highly flammable liquid and vapour. H225 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. H373 H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. R11 Highly flammable. R36 Irritating to eyes. R38 Irritating to skin. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. R62 R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. R67 Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

(Contd. on page 16)

Printing date 24.06.2014

Revision: 24.06.2014

(Contd. of page 15)

Trade name: Buffing Solution (Rubber Cleaner)

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 • **Sources** SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com