

FRESNO

 Ceiling mounted • Dry location listed **PROGRESS LED**

Description:

Five-blade 60" Fresno ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. A white opal glass shade features an 18W dimmable, 3000K LED module. Full range dimming and remote control with batteries is included. Featuring reversible blades, the fan has a Brushed Nickel finish. Can be used to comply with California Title 20. Can be used to comply with 2016 Title 24 JA8.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- White opal glass bowl
- Fresno ceiling fan features reversible Silver/Black blades with a Brushed Nickel finish
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- The light kit contains a white opal glass shade and is comprised of a 18W dimmable 3000K LED module, offering 1400 lumens, 90+ CRI
- A full function remote with batteries is included - and controls full range dimming and fan speed capabilities including reverse
- Oversized ceiling fan ideal for use in spacious areas, such as large great rooms, living rooms, bedrooms and bonus rooms
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that is larger than 400-square feet
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately
- Mounting hardware is included
- Can be used to comply with California Title 20.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 80" of wire supplied
- Silver/Black reversible blades, plywood construction
- 14 degree blade pitch
- Full Function Remote Included
- Triple capacitor speed control
- Meets California Title 24 JA8-2016 Airflow: 5718 CFM*
- Energy consumption: 79 watts (excluding lights)*
- Airflow efficiency: 72 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1400/77.8 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016

P2548-0930K

Images:



Dimensions:

Diameter: 60"
Height: 17-1/4"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$14

\$3 | | | \$34

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6.4 hours use per day
• Your cost depends on rates and use
• Energy Use: 50 Watts

All estimates based on typical use, excluding lights

Airflow

4029

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
• Airflow Efficiency: 80 Cubic Feet Per Minute Per Watt

ftc.gov/energy

P2548-0930K

Dimming Notes:

P2548 is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

"Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW"

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.