



Oatey®

3"-4" GALVANIZED ALL-FLASH® NO-CALK® ROOF FLASHING

#11862

1. Remove existing flashing. Use new flashing as is with a 3" pipe.
2. For use with 4" pipe, remove the inner ring on the collar as shown.
3. Chamfer vent stack. Once chamfered, push the All-Flash over the vent stack and secure to roof with nails along sides and corners. Slide the base under the shingles.



⚠ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

⚠ **AVERTISSEMENT:** Cancer et Troubles de l'appareil reproducteur - www.P65Warnings.ca.gov

⚠ **ADVERTENCIA:** Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov

Assembled in U.S. of U.S. and foreign components
Assemblé aux É.-U. avec des composants américains et étrangers
Ensamblado en EE.UU. con componentes de EE.UU. y otros países

Oatey Co. Cleveland, OH 44135

800-321-9532 • Oatey.com

#93223B 8/18



Dimensions: 4" w x 3" h
Colors: Pantone 185 Red + Black

Oatey Cleveland, Ohio 44135 800.203.1155 Oatey.com		ALL ARTWORK IS THE PROPERTY OF OATEY CO. AND SHALL NOT BE REPRODUCED OR DISTRIBUTED WITHOUT OFFICIAL WRITTEN PERMISSION FROM OATEY CO.
Refer to Dimensional Specification - 93223		
Colors: ■ Black ■ PMS 185	☒ Top Coat	DESCRIPTION #11862 - Oatey 3-4" Galvanized All-Flash No-Calk Roof Flashing label
		DESIGNER: Pauline Yee (pyee@oatey.com)