

Armstrong®
CEILING

stains
away!

Specialty
coating
designed to
match Armstrong®
ceilings!

Conceals water
and smoke stains

Dries quickly with
low odor

Sprays from
any angle

See additional precautions on back panel.
KEEP OUT OF REACH OF CHILDREN.

DANGER: EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.

NET WT. 12 OZ. (341G)

Contains/CAS: Propane/74-98-6, Butane/106-97-8, Ethyl Acetate/141-78-6, Acetone/67-64-1, VM&P Naptha/68410-97-9,
Titanium Dioxide /13463-67-7, VM&P Naptha/64742-89-8.

STAINSAWAY!™ SPECIALTY COATING

A designed color match for all white Armstrong® ceiling tiles, StainsAway! specialty coating can be used to revive the appearance of your Armstrong ceiling tiles. When used as directed, StainsAway! specialty coating may also extend the practical life of ceiling tiles by keeping them looking like new!

DIRECTIONS FOR USE

Read cautions and directions carefully before using. When spraying suspended ceilings, cover everything beneath/under area with cloth or newspaper. Test StainsAway! specialty coating in an obscure, small area first to determine color match. StainsAway! specialty coating should be shaken well as it contains extremely high amounts of solid material.

1. Shake can well for 2 minutes after marble rattles. Shake occasionally during use.
2. Hold can about 8-12 inches from surface and spray light coats over discolored area. Repeat.
3. If clogging develops twist off the spray button and clean in thinner. Do not stick pins or other objects into can valve.

Warning if you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the Nation Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. For a CPSIA Conformity Certificate contact www.paintcompliance.com.

Vapors may ignite explosively. Vapor may cause flash fire. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or stove at temperatures above 120 degrees F.

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. HARMFUL IF SWALLOWED. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

WARNING: This product contains a chemical known to the state of California to cause cancer.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

DISPOSAL: Dispose of container and unused contents in accordance with local, state and federal regulations.

PWMIR for Flat Paint 1.20 VOC Max. 60%.

KEEP OUT OF REACH OF CHILDREN.

Manufactured in the U.S.A. for
Armstrong World Industries, Inc.,
Lancaster, PA 17603
1-877-ARMSTRONG (276-7876)
©2016 AWI Licensing LLC

For more information on Armstrong ceiling products,
please visit armstrongceilings.com

