

Assembly Instruction Sheet #S-1343P3
For Style 1343P3


Total Weight: 14.5lb (6.6kg), Philips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (1) 15W LED 9 W DIMMABLE (not inc)

Estimated Assembly Time: 15-30 minutes
Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

Warnings and Cautions

Turn off electricity at circuit breaker or main line box before installation. Consult a licensed electrician if in doubt.
These instructions are provided for your safety. It is very important you read them completely before installing the fixture.
We strongly recommend that a licensed, professional electrician perform the installation.
Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents



Hardware Contents

HW	DESCRIPTION	QUANTITY
BB	Decorative Cap	2pcs
CC	Outlet Box Screw	2pcs

STEP 1 – Attach Mounting Screws, Lock Washers and Hex Nuts to Mounting bracket.




Figure 1

STEP 2 – Attach Mounting bracket to Outlet Box
A) Pass the supply wires through the Mounting bracket (EE). Attach the Mounting bracket (EE) to the Outlet Box with the head of the Green Ground Screw facing you. Secure it with Outlet Box Screws. Tighten until snug.




Figure 2

STEP 3 – Fit Backplate to Mounting bracket Assembly
A) Fit the backplate to Mounting Screws (DD) and secure with Decorative Caps (AA). Note: The backplate should be snug against the ceiling and the Decorative Caps (AA). If not, adjust the length of the Mounting Screws (DD) by unscrewing the Hex Nut and Lock Washer and then screwing Mounting Screws (DD) in or out of the Mounting bracket (EE) until the correct length is achieved. Once the Ceiling Canopy is secure, remove the Decorative Caps (AA) and Ceiling Canopy and proceed to Step 4





Figure 3

STEP 4 – Wire Connections



4. Fix the glass B on the lamp body A with screw D
5. Place iron bracket knob A1 on lamp body A
6. Fix acrylic sheet C on lamp body A with aluminum A2




Figure 5

STEP 6 - Install Ceiling Canopy to Ceiling
A) Carefully tuck all wires into the outlet box and position the ceiling canopy of the Fixture Body (A) over the outlet box. Align the holes in the ceiling canopy with the Mounting Screws (DD). Secure with Decorative Caps (AA) and hand tighten until snug.




Figure 6