

CLEAR MATTE FINISH

# DRYLOK®

## NATURAL LOOK

### WALK & DRIVEWAY SEALER

CURING COMPOUND THAT SEALS AND PRIMES IN ONE



BRICK



CONCRETE



STONE

Strengthens freshly poured concrete by slowing set time  
Repels water and resists stains  
Protects against cracking, delamination, and spalling

WILL DARKEN  
SURFACE BUT  
APPEAR DRY  
WITH NO SHEEN

BEFORE

AFTER

VOC: 92 g/L



#### DRYLOK® NATURAL LOOK

Meets A.S.T.M. Specification C-309

DRYLOK® Natural Look is a dual-purpose coating designed for curing and sealing new concrete and sealing existing concrete. DRYLOK® Natural Look will also solidify powdery and chalking concrete and masonry prior to painting. It is ideal under latex, alkyd, or polyurethane concrete floor paints or carpeting. Note: for self-adhesive floor tiles, check with tile manufacturer for adhesion compatibility.

**SURFACE PREPARATION:** When using as a sealer only, clean the surface, check the porosity to promote coating absorption. Do not use this product on non-porous, sealed, or painted surfaces. Oil stains, dirt, and other surface contaminants must be removed. Scrub with DRYLOK® Etch according to manufacturer's directions or use a heavy-duty detergent in warm water. Cleaners must be followed by rinsing and drying. Unsound, flaking concrete should be removed or repaired. Smooth concrete must be etched and feel like medium grit sandpaper to properly accept the coating. Note: Rinse etching solutions thoroughly. Etching solutions allowed to dry on masonry surfaces prevent proper curing.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** DRYLOK® Natural Look appears milky in the can but dries clear.

**CONCRETE CURING MEMBRANE:** When applying as a curing membrane, apply to new concrete after finishing when the new concrete has hardened and the surface sheen has disappeared. This will depend on atmosphere and weather conditions. Do not apply to finished concrete surface too quickly. Using a garden sprayer, apply 2 thin layers at right angles to one another. Apply evenly to obtain coverage of 200 ft²/gal (4.9 m²/L). Do not leave puddles. Use a brush to spread excess and remove puddles.

**SEALING:** Do not apply if rain, heavy dew, or temperature below 50°F (10°C) are expected within 24 hours before or after application. Apply by brush, roller, or sprayer. Roller: 1/4"-3/8" nap roller; brush: nylon/polyester; garden sprayer. Apply to dry concrete or masonry. Spread evenly – do not allow puddles or a heavy surface film to occur. Apply one coat using thin

even strokes. Extremely porous surfaces may require a second coat. Allow 3 hours drying time between coats. **Not for use on asphalt surfaces.**

**THINNING:** When applied over flagstone, slate, terrazzo, dense smooth or light colored concrete, thin with clean, moderately warm water 10%-20% to minimize sheen variations as subsequent top coats are applied. Test on a small area to see final effect.

**COVERAGE:** Up to 400 sq. ft. (37 m²) per gallon depending on surface porosity.

**CLEAN UP:** Soap and water.

**DRY TIME:** Allow to dry 2 hours before subjecting to light foot traffic and 24 hours before subjecting to heavy traffic. Do not cover surfaces treated with DRYLOK® Natural Look for at least 24 hours after application. Drying time can be affected by temperature, humidity, and film thickness.

**CAUTION:** Do not take internally. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal guidelines.

**FIRST AID:** In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Call poison control center, hospital emergency room, or physician immediately. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately.

**KEEP FROM FREEZING!**  
**KEEP OUT OF REACH OF CHILDREN.**  
**USE ADEQUATE VENTILATION.**  
**DO NOT TAKE INTERNALLY.**

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

UNITED GILSONITE LABORATORIES, 1396 Jefferson Ave., Dunmore, PA 18509  
Order No. 22113 UFI: JY5J-HCCQ-960Y-2YTN LR923 [www.DRYLOK.com](http://www.DRYLOK.com)

**UGL** UNITED GILSONITE LABORATORIES

A SIKA COMPANY



LATEX  
FILM-FORMING  
SEALER



PATIOS &  
PORCHES



GARAGE  
FLOORS



WALKS &  
DRIVEWAYS

HORIZONTAL  
& VERTICAL  
APPLICATIONS



MADE IN USA

1 GALLON (3.785 L)

R6567