

QC CL-2250 RF QuietCool Original Classic Line

QC CL-2250 RF Specifications

Airflow	Hi: 2,465 CFM / Low: 1,910 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 1,770 CFM / Low: 1,330 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 822 SQFT to 1,233 SQFT	
Energy Use	Hi: 250 Watts / Low: 201 Watts	
Amps	Hi: 2.47 / Low: 1.90	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 43.2 / Low: 37.4	
Minimum Attic Clearance	34"	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	3.29 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 18 1/4"	
Removable Grille Outside Dimension	16" x 20"	
Shipping Weight	48 lbs.	
Box Dimensions	24" x 20" x 38"	
In The Box	-QC CL-2250 Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -6 Foot Duct -Accessory Bag -Wireless RF Control Kit	



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM