


Stem Mount Outdoor Light Control with Photocell



SPECIFICATIONS

PHOTOCONTROL TYPE:	Electronic	SENSOR TIME DELAY:	Instant on; 30-120 seconds off
APPLICATION COMPATIBILITIES:	LED; Incandescent; HID	FAIL MODE:	On
PHOTOCONTROL STYLE:	Stem Mount	ACTIVATION ON:	1.0 fc
PHOTOCONTROL SENSOR LOCATION:	Side	ACTIVATION OFF:	1.5 fc
HOUSING MATERIAL:	Aluminum		
PRODUCTION DIMENSIONS:	3.5" H x 1.5" L x 2" D		
WEIGHT:	.33 lbs.	VOLTAGE:	120
WIRE LENGTH LEAD:	6"	TUNGSTEN RANGE:	2000 W
WIRE SIZE MAX:	#16 AWG	BALLAST:	2000 VA
THREADED STEM SIZE:	1/2"	TEMPERATURE OPERATION:	-40°F to 140°F

WARRANTY:	5-Year limited warranty
UL/ETL CERTIFICATION:	UL
WET/DRY/DAMP LISTING:	Wet
ROHS CERTIFICATION:	Yes
IP GRADE:	IP54



TYPE:
JOB:
ORDER CODE:
APPROVALS: