

Installation instructions 7 US

CA

Product dimensions	RF135B		E522B	
	inches	mm	inches	mm
A overall height of flat door product	67 ¹⁷ / ₃₂	1715	67 ¹⁷ / ₃₂	1715
A overall height of curved door product	–	–	66 ¹⁵ / ₁₆	1700
A overall height of curved door with ice & water product	–	–	67 ¹ / ₈	1705
B overall width of product	25	635	31 ³ / ₃₂	790
C overall depth of flat door product (excludes handle, includes evaporator)	27 ³ / ₈	695	27 ³ / ₈	695
C overall depth of curved door product (excludes handle, includes evaporator)	–	–	28 ³ / ₃₂	715
Cabinetry dimensions (including minimum clearances)				
D inside height of cavity	68 ⁵ / ₁₆	1735	68 ⁵ / ₁₆	1735
Flush with refrigerator chassis – full door rotation				
E inside width	26 ⁹ / ₁₆	675	32 ¹¹ / ₁₆	830
F inside depth	24 ¹³ / ₃₂	620	24 ¹³ / ₃₂	620
Flush with refrigerator door – full door rotation				
G inside width	31 ³ / ₃₂	790	37 ⁷ / ₃₂	945
H inside depth flush to curved door	–	–	26 ²⁵ / ₃₂	680
I inside depth flush to flat door	27 ³ / ₈	695	27 ³ / ₈	695
Flush with refrigerator door – 90° door rotation (for full drawer/shelf access, the doors need to be open past 90°)				
J inside width	29 ¹¹ / ₃₂	745	35 ⁷ / ₁₆	900
K inside depth flush to curved door	–	–	26 ²⁵ / ₃₂	680
L inside depth flush to flat door	27 ³ / ₈	695	27 ³ / ₈	695
Minimum clearances				
M side clearance	2 ⁵ / ₃₂	20	2 ⁵ / ₃₂	20
N side clearance – hinge side flush with door – full rotation	5 ⁵ / ₁₆	135	5 ⁵ / ₁₆	135
O side clearance – hinge side flush with door – 90° rotation	3 ¹⁷ / ₃₂	90	3 ¹⁷ / ₃₂	90
P rear clearance (incl. evaporator tray)	1 ³ / ₁₆	30	1 ³ / ₁₆	30
Q vent – around top of cupboard (optional)	1 ³ / ₃₂	50	1 ³ / ₃₂	50
R top clearance – above refrigerator cabinet	1 ³ / ₃₂	50	1 ³ / ₃₂	50
S door clearance – hinge side flush with chassis – full rotation	20 ¹⁵ / ₃₂	520	25 ¹³ / ₃₂	645
T door clearance – hinge side flush with door – full rotation	15 ¹⁵ / ₁₆	405	20 ⁷ / ₈	530