

Installation Instructions:

Remove parts from package. Check that all parts are included.
Hook up to cold water valve only.

- i. "Y" Connector
- ii. Short inlet hose
- iii. Fill hose with 90° elbow

1. Turn off cold water supply at shut-off valve and disconnect existing washing machine hose.
2. Attach short hose to cold water valve. Hand tighten connection, then an additional one-half turn lightly with pliers.
NOTE: Do not over tighten. Damage to the coupling nut can result.
3. Attach "Y" connector to short hose.
4. Attach straight end of long hose to "Y" connector.
5. Re-attach washer cold inlet hose to other end of "Y" connector. Hand tighten connection, then an additional one-half turn using pliers.
NOTE: Do not over tighten. Damage to the coupling nut can result.
6. Attach elbow end of long hose to fill valve on the back of the dryer back panel. Hand tighten connection, then an additional one-half turn with pliers.
NOTE: Do not over tighten. Damage to the coupling nut can result.
7. Turn on water supply. Check "Y" connector, faucet and hoses for leaks.
8. Slide dryer into place taking precautions not to kink or stretch fill hose. Ensure connector is not exposed to heat, open flame or corrosive agents.
CAUTION: Ensure rubber washers are inserted into the ends of each connector before installing.

SPECIFICATIONS:

15°F to 158°F working temperature, 200 PSI max working pressure.
Surpasses all requirements for flexible water connectors, as defined by ASME A112.18.6 and CSA B125.

WARNING:

This connector is to be used with water in exposed locations only. Clean with water only. Do not expose to household cleaners or other corrosive chemicals. Keep away from heat. Do not connect to instant hot water heaters. Do not reuse. Replace every 5 years.

CALIFORNIA PROPOSITION 65 WARNING

This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

