



René

872.241.0016

Toledo, Ohio

sales@renesinks.com

Renesinks.com

DUAL MOUNT SINKS

Installation Guide

THE INSTALLATION OF SINKS

WHICH CAN BE UNDERMOUNTED OR TOPMOUNTED

Some sink models constructed of copper, bronze, and composite granite have the option of being mounted either under or over the countertop. Their wide and tapered rims allow either type of installation.





872.241.0016

Toledo, Ohio

sales@renesinks.com


Renesinks.com

DUAL MOUNT SINKS

Installation Guide



UNDERMOUNT TECHNIQUES



Note: Topmounting does not require clips.

THE STEPS

- Using the template provided, measure and cut the hole in the countertop.
- Undermount: Determine the locations for the clip brackets around the perimeter of the sink. Pre-drill holes for the clips using appropriate methods for the countertop material.
- With denatured alcohol, clean the surfaces of the sink and countertop which will meet.
- Topmount: Apply a bead of silicone along the top perimeter edge of the counter opening.
- Undermount: Apply a bead of silicone along the perimeter edge of the opening on the underside of the counter.
- Topmount: Carefully align the sink over the countertop opening and lower into position, applying pressure to secure a seal of the silicone against the countertop.
- Undermount: Carefully align the sink under the countertop opening and raise into position, applying pressure to secure a seal of the silicone against the countertop.
- Re-check that the sink is evenly aligned with the countertop.
- Undermount: Attach and tighten the clip brackets against the edge of the sink. Do not tighten one screw completely before others. Partially tighten one clip then the one across from it, and so on until all clips are fully tightened. This will safeguard against an uneven or insecure installation.
- Use a cloth with denatured alcohol along the perimeter of the sink and countertop to remove any excess sealant.

