
## PRODUCT SPECIFICATION DRAWING <u>EvoPEX Copper Stub Outs</u>





Part	Description	Α	В
K25811	Copper Stub Out with Bracket & EvoPEX 1/2" 90	6.82	2.44
K25813	Copper Stub Out with EvoPEX 1/2" 90	6.82	
K25815	Copper Stub Out with Bracket & EvoPEX 1/2" 90	8.83	2.44
K25817	Copper Stub Out with EvoPEX 1/2" 90	8.83	

Minimum working temperature: 33°F @ 160 psi

Maximum working temperature: 200°F @ 80 psi Maximum working pressure: 160 psi @ 33°F - 70°F

SharkBite EvoPEX fittings are for use in residential and commercial applications. SharkBite EvoPEX fittings are only for use with PEX tubing and have a 25-year warranty when used with SharkBite PEX tubing. Proper tubing insertion depth determined by integral green indicator ring. SharkBite EvoPEX fittings are approved for use in the following applications:

Temperature & Pressure Rating:

-Potable water -Recirculation (140F max) -Radiant heating -Direct burial\*

## **Product Information:**

Material:

PEX Material: Type L Copper

SharkBite Material: Body: Acudel

> Collet: Fiber reinforced nylon Collet Retainer: SST 304

O-ring: EPDM
Grab ring: SST 316
Protection ring: Copolymer

Spacer: Copolymer

Certifications/Listings:

-ANSI/NSF 14 -ASTM F876 -ASTM F877 -CSA B137.5 -NSF/ANSI/CAN 61

Code approvals: UPC, UMC, IPC, IMC, IRC, NPC of Canada, NBC of Canada, NSPC

*	Fitting Type	Silicone Wrap Required
,	SharkBite Universal fittings (1/4" - 2")	Yes
	EvoPEX fittings - with brass bodies	Yes
	EvoPEX fittings - with all polymer bodies	No

For methods of installation and warranty information, visit www.sharkbite.com

THIS INFORMATION IS PROPRIETARY TO RWC AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT MAY NOT BE REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION.



Product Submittal

Job Name:

Date:
Part Number: Qty:

Architect / Owner:

Contractor:

Notes:

Reliance Worldwide Corporation (RWC) / 1-877-700-4242 / www.sharkbite.com spec\_EvoPEX Stub Outs Series, RevA, 02-05-20