File E523118 Project 4789978132

> June 30, 2021 REPORT

> > On

LAMPHOLDERS, CANDELABRA AND MINIATURE

Dongguan Nuobaoxin Lighting Technology Co., Ltd. Guangdong, China

Copyright © 2021 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

File E523118

Vol. 1

Index

Page 1

Issued: 2021-06-30

INDEX

SECTION	PRODUCT COVERED	USL	CNL
1	Candelabra Lampholders, Models	Х	Х
	NBX-12A, NBX-12B, NBX-12C		

File E523118 Vol.1 OMFV Page 1 Issued: 2008-06-05 Listing Mark Data Page (LMDP)

(FILE IMMEDIATELY AFTER AUTHORIZATION PAGE)

LISTING MARK

The Listing Mark consists of four elements placed in close proximity and shall appear on Listed products only. Minimum size is not specified, as long as the Listing Mark is legible. The following is suggested.



XXXX = The control number assigned by UL, E523118.

The minimum height of the registered trademark symbol \circledR shall be 3/64 of an inch. When the overall diameter of the UL Mark is less than 3/8 of an inch, the trademark symbol may be omitted if it is not legible to the naked eye.

The product identity is: "LAMPHOLDER", "MINIATURE LAMPHOLDER" or "CANDELABRA LAMPHOLDER."

The product identity may be omitted if the Mark is directly and permanently applied to the product by stamping, molding, ink-stamping, silk screening or similar process. The product identity may appear elsewhere on the product if the other three elements are part of the nameplate which includes the rating or the catalog or model designation.

Separable Listing Mark (not part of a nameplate and in the form of decals, stickers or labels) will always include the four elements.

The complete four-element Listing Mark will appear on the smallest unit container in which the product is packaged when the product is of such a size that only the UL Symbol can be applied to the product or when the product size, shape, material or surface texture makes it impossible to apply any legible marking to the product.

The manufacturer may reproduce the Mark or obtain it from a UL authorized supplier. The list of UL authorized label suppliers can be found on UL's online directory at www.ul.com.

THIS FORM PAGE IS TO BE REVISED BY THE NORTHBROOK LABEL DEPARTMENT ONLY



File E523118 Vol.1 OMFV7 Page 1 of 2 Issued: 1/2/98 Canadian Listing Mark Data Page (CLMDP)

(FILE IMMEDIATELY AFTER AUTHORIZATION PAGE)

LISTING MARK

The Listing Mark consists of four elements placed in close proximity and shall appear on Listed products only. Minimum size is not specified, as long as the Listing Mark is legible. The following is suggested. (If only Canadian coverage is authorized, use only the C-UL Symbol).

UL Symbol to the left and the C-UL Symbol to the right.



LISTED (PRODUCT IDENTITY)



Alternatively, the Canadian/US Mark may be used. The UL Symbol with "C" to the left and "US" to the right.



XXXX = The control number assigned by UL, E523118.

The minimum height of the registered trademark symbol \circledR shall be 3/64 of an inch. When the overall diameter of the UL Mark is less than 3/8 of an inch, the trademark symbol may be omitted if it is not legible to the naked eye.

The product identity is: "LAMPHOLDER", "MINIATURE LAMPHOLDER", or "CANDELABRA LAMPHOLDER".

The product identity may be omitted if the Mark is directly and permanently applied to the product by stamping, molding, ink-stamping, silk screening or similar process. The product identity may appear elsewhere on the product if the other three elements are part of the nameplate which includes the rating or the catalog or model designation.

Separable Listing Mark (not part of a nameplate and in the form of decals, stickers or labels) will always include the four elements.

THIS PAGE IS TO BE REVISED BY FUS DEPARTMENT ONLY

THIS FORM PAGE IS TO BE REVISED BY THE NORTHBROOK LABEL DEPARTMENT ONLY

File E523118

Vol. 1

Sec. 1 and Report

Page 1 Issued: 2021-06-30

DESCRIPTION

PRODUCT COVERED:

USL, CNL - Candelabra base lampholders, Models refer to ELECTRICAL RATINGS table.

For use in dry or damp location.

ELECTRICAL RATINGS:

Model	Rating	
NBX-12A	125 V, 75 W	
NBX-12B		
NBX-12C		

ENGINEERING CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE USE):

USL - Products designated USL have been investigated using US requirements as noted in the Test Record.

 ${\tt CNL}$ - Products designated CNL have been investigated using Canadian requirements as noted in the Test Record.

Lampholder Models NBX-12A, NBX-12B, NBX-12C have molded plastic body with integral molded screwshell and contacts made of copper alloy and stainless steel. They are keyless and unswitched.

