

BISCUIT

BISCUIT

BISCUIT

BISCUIT

BISCUIT


Kwik Seal Plus®

CAUTION! Contains ethylene glycol. May cause mild skin irritation. Do not get in eye, on skin, or on clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **FIRST AID: SKIN:** Wash thoroughly. **EYE:** Immediately flood with large quantities of water. **INHALATION:** Remove to fresh air. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **In an emergency,** call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN. ¡PRECAUCIÓN!** Contains ethylene glycol. May cause mild skin irritation. Do not get in eye, on skin, or on clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **PRIMEROS AUXILIOS: PIEL:** Lávese muy bien. **OJOS:** Lavar con abundante agua. **INHALACIÓN:** Salir al aire fresco. **INGESTIÓN: NO INDUZCA EL VÓMITO.** Busque atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Refiérase a la Ficha de Datos sobre Seguridad (SDS, por sus siglas en inglés) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

▲ WARNING Cancer and Reproductive Harm / **ADVERTENCIA** Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5% wt/wt
(25.2 g/L)



DAP Products Inc.
Baltimore, MD 21224

Made in the USA with
U.S. and globally
sourced materials.

dap.com

Kwik Seal Plus®

Premium Kitchen & Bath Adhesive Sealant

MOLD GUARD
TECHNOLOGY

Fights the Growth of Stain & Odor-Causing Mold & Mildew on the Sealant

- 100% Waterproof
- Crack Proof Guarantee
- Paintable
- Easy Water Clean-up & Low Odor

Kitchen, Bath & Plumbing

Kwik Seal Plus®

DAP® KWIK SEAL PLUS® Premium Kitchen & Bath Adhesive Sealant contains MoldGuard Antimicrobial Product Protection to fight the growth of stain & odor causing bacteria, mold & mildew on the sealant. The sealant is easier to clean & stays cleaner between cleanings. Provides excellent flexibility & adhesion for durable, 100% waterproof seal. Paintable.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at 45° angle to desired bead size. 3. Load cartridge into caulk gun. 4. Fill gap or joint with sealant. 5. Smooth bead. 6. Clean up excess wet sealant with a damp sponge before it skins over. Clean hands & tools with warm water. Excess dried sealant must be cut or scraped away. 7. **PAINTABLE.** Allow sealant to dry at least 2 hours (longer in cool/humid conditions) before painting with latex or oil-based paints. 8. Wait 18 hours before exposing to water. 9. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead

CRACK PROOF GUARANTEE: DAP warrants that this product will not mildew, crack, peel or separate, when used as directed within one year of purchase. If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be liable responsible for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com

QUESTIONS? ¿PREGUNTAS? Call/Llame al 888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 fl oz (300 mL)