

Café™ 30" Smart Slide-In Front-Control Induction and Convection Range

C A F É

CHS90XM2NS5



FEATURES & BENEFITS

Harness a sense of control – Turn any pan into a smart pan and automatically maintain a set temperature within one degree thanks to a cooktop sensor that gives you total control from either the display or your smartphone

You've got an eye for perfect timing – Monitor the progress of time-sensitive dishes without needing to open the oven door with an in-oven camera that provides an interior view of cooking food visible from your smartphone

Precision is the name of your cooking game – Confidently try new recipes and perfectly execute your favorites using a smart system that automatically tracks progress, modifies temperatures and adjusts cook times

A touch of brilliance – Bring interactive capabilities into your kitchen with a 7" LCD touch screen that looks stunning and makes it easy to control your oven

Design that pushes boundaries – Extraordinary design meets outstanding functionality thanks to a push-to-open storage drawer that eliminates the need for an additional handle on your range's façade, creating a unique, sleek aesthetic in your kitchen

Enjoy total control in the kitchen and beyond – Control your oven with your smart device or simply your voice using WiFi Connect

APPEARANCE

Color Appearance	Stainless Under Glass
Handle	Café Minimal Style; Stainless Steel
Installation	Flush Appearance; Free-standing cut-out
Oven Door Features	Big-View Oven Window; Full-Wrapped Metal Frame; Full-Wrapped Stainless
Textured Steel Side Panels	Yes
Handle Color	Stainless Steel

FEATURES

Cooktop Burner Type	Induction
Cooktop Surface	Edge-to-Edge; Gray Patterned Ceramic Glass
Element - Left Front	8" 2500W Sync Element with Temp Sensor
Element - Left Rear	8" 2500W Sync Element
Element - Right Front	11" 3700W Power Boil
Element - Right Rear	6" 1800W
Element - Center	6" 100W Warming Zone
Configuration	Range
Control Location	Front Controls
Hot Surface Indicator Lights	1
Oven Cleaning Type	Steam Clean
Oven Control Features	Audible Preheat Signal; Auto Oven Shut-Off with Override; Auto Recipe Conversion; Auto Self-Clean; Certified Sabbath Mode; Chef Connect; Control Lock Capability; C° or F° Programmable; Delay Bake Option (Time Bake); Delay Clean Option; Electronic Clock & Kitchen Timer; Fast Preheat; Hi / Low Broil; Oven "ON" Light; Oven Camera; Pan Temperature Sensor; Precision Cooktop Sensor; Self-Clean Cool Down Time Display; Steam Clean; Temperature Probe
Oven Cooking Modes	Convection Bake Multi-Rack; Convection Roast; Precision Cooking Modes; Proof; Warming
Self-Clean Oven Door Lock	Automatic
Control Type	Digital Temperature Display; Electronic; Glide Touch; Touchpads
Cooking System	True European Convection with Precise Air
Heating Element "ON" Indicator Light	5
Oven Features	8-Pass Broil Element; Hidden Bake
Oven Rack Features	1 Self-Clean Heavy-Duty Roller Rack; 2 Self-Clean Heavy-Duty Oven Racks; 6 Rack Positions
Connected Capabilities	Amazon Alexa; DiGiorno; Drop; Hestan Cue; IFTTT; Innit; Nest; The Google Assistant
Melt Setting	Yes
WiFi Connect	Built-In
Cooking Technology	Convection
Oven Interior	1 Incandescent; Black; In-Oven Camera

CAPACITY

Total Capacity (cubic feet)	5.3 cu ft
-----------------------------	-----------

ACCESSORIES

Trim Kit	JXFILLR1SS - Optional
Air Fry Basket	JXAFTRAY1VSS - Optional
Probe Accessory	JXPROBE1 - Optional

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	221 lb
Cabinet Width	30 in
Depth with Door Open	48 1/4 in
Depth Without Handle	26 7/8 in
Net Weight	200 lb
Oven Interior Dimensions (W x H x D) (in.)	24 x 19 7/8 x 20 5/8
Overall Depth	29 1/2 in
Overall Height	37 1/4 in
Overall Width	29 7/8 in
Height to Top of Rear Vent Trim	37 1/4 in
Height to Cooking Surface (in.)	36 +/- 1/4 in

Café™ 30" Smart Slide-In Front-Control Induction and Convection Range



CHS90XM2NS5

POWER / RATINGS

Amp Rating at 208V	40
Amp Rating at 240V	40
Bake Wattage	2850W
Broiler Wattage	4000W
Convection Wattage	2500W
KW Rating at 208V	10.4
KW Rating at 240V	12.5

WARRANTY

Parts Warranty	Limited 1-Year Entire Appliance
Labor Warranty	Limited 1-Year Entire Appliance
Warranty Notes	See Written Warranty for Full Details

DIMENSIONS

Receptacle Locations: Locally approved flexible service cord or conduit must be used because terminals are not accessible after range installation. See shaded area in drawing for location of electrical outlet box. Recommended outlet locations allow range to be installed directly against rear wall.

Note: This appliance has been approved for 0" spacing to adjacent surfaces above the cooktop. However, a 6" minimum spacing to surfaces less than 15" above the cooktop and adjacent cabinet is recommended to reduce exposure to steam, grease splatter and heat.

Installation Information: Before installing, consult installation instructions for current dimensional data and additional requirements.

