



# 1. Identification

Product identifier	KILZ® OVER ARMOR Textured Wood & C	oncrete Resurfacer - Slate Gray		
Other means of identification				
Product number	L3957			
Recommended use	Architectural Coating			
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier	Distributor information			
Supplier	Masterchem Industries LLC			
	3135 Old Highway M			
	Imperial, MO 63052-2834			
Telephone	636-942-2510			
Emergency telephone	+1 760 476 3962			
	+1 866 519 4752			
Access code	335213			
2. Hazard(s) identification				
Physical hazards	Not classified.			
Health hazards	Serious eye damage/eye irritation	Category 2A		
	Sensitization, skin	Category 1A		
	Carcinogenicity	Category 2		
OSHA defined hazards	Not classified.			
Label elements				
Signal word	Warning			
Hazard statement	May cause an allergic skin reaction. Causes	serious eye irritation. Suspected of causing cancer.		
Precautionary statement				
Prevention	and understood. Avoid breathing mist/vapors	ot handle until all safety precautions have been read b. Wash thoroughly after handling. Contaminated workplace. Wear protective gloves/protective		
Response	Remove contact lenses, if present and easy medical advice/attention. If skin irritation or ra	es: Rinse cautiously with water for several minutes. to do. Continue rinsing. If exposed or concerned: Get ash occurs: Get medical advice/attention. If eye on. Wash contaminated clothing before reuse.		
Storage	Store locked up.			
Disposal	Dispose of contents/container in accordance	with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.			
Supplemental information	None.			
3. Composition/information	on on ingredients			

**Mixtures** 

Chemical name	CAS number	%
Quartz (Crystalline silica)	14808-60-7	10 - 30

Titanium dioxide		13463-67-7	3 - 7
Mica		12001-26-2	1 - 5
Poly(oxy-1,2-ethanediyl), a-sulfo-w-hydroxy-, C12-14-akyl ethers, sodium salts		68891-38-3	1 - 5
3-(2-aminoethylamino)propyln ethyldimethoxysilane	1	3069-29-2	0.1 - 1
3-lodo-2-propynyl butylcarbamate		55406-53-6	0.1 - 1
Carbon black		1333-86-4	0.1 - 1
Diuron		330-54-1	0.1 - 1
Maleic anhydride		108-31-6	0 - 0.1
Composition comments	All concentrations are in percent by weigh percent by volume.	nt unless ingredient is a gas. Ga	s concentrations are in
	The manufacturer has claimed the exact Communication Standard.	percentage as trade secret unde	er the OSHA Hazard
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.		
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.		
Ingestion	Rinse mouth. Get medical attention if symptoms occur.		
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.		
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder.	Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, a	is this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.		
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.		
General fire hazards	No unusual fire or explosion hazards noted.		
6. Accidental release meas	sures		
Dereenal pressutions	Koon uppersonny personnel away Koor	people away from and upwind	of anill/look Moor

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for	This product is miscible in water.
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### **Occupational exposure limits**

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

g/m3
Form
/m3
m3 Total dust.
Form
ocf
/m3 Respirable.
pcf Respirable.
n3 Respirable fraction.
m3 Total dust.
ocf Total dust.
cf Respirable fraction.
Form
13 Inhalable fraction.
m3
n3 Respirable fraction.
ng/m3 Respirable fraction.
m3
r Fin r r r

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable.
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ological limit values	No biological exposure limits noted	for the ingredient(s).	
propriate engineering ntrols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
lividual protection measures	, such as personal protective equipr	nent	
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection Hand protection	Wear appropriate chemical resistant gloves.		
Skin protection Other	Wear appropriate chemical resistan	t clothing. Use of an impervious	apron is recommended.
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for ar uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
eneral hygiene nsiderations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		

# 9. Physical and chemical properties

Appearance		
Physical state	Liquid.	
Form	Liquid.	
Color	Gray.	
Odor	Slight.	
Odor threshold	Not available.	
рН	7 - 10	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	> 99 °F (> 37.2 °C)	
Flash point	Not applicable.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not applicable.	
Upper/lower flammability or explosive limits		
Flammability limit - lower Not available. (%)		
Flammability limit - upper (%)	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	1.42	
Solubility(ies)		
Solubility (water)	Soluble.	

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 140 KU at 25°C
Other information	
Density	11.85 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	42 g/l (excluding water) (Coating) 23 g/l (including water) (Material)

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
3-lodo-2-propynyl butylcark	bamate (CAS 55406-53-6)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	1.1 g/kg
Carbon black (CAS 1333-8	36-4)	
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Oral		
LD50	Rat	> 8000 mg/kg
Quartz (Crystalline silica) (	CAS 14808-60-7)	
<u>Chronic</u>		
Inhalation		
LOEC	Human	0.0563 mg/m3

Components	Species	Test Results
Titanium dioxide (CAS 13463-67-7)	)	
Acute		
Inhalation		
LC50	Rat	3.43 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may ca	ause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin rea	action.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall E	valuation of Carcinogenicity	
Carbon black (CAS 1333-8 Quartz (Crystalline silica) ( Titanium dioxide (CAS 134 NTP Report on Carcinogens	(CAS 14808-60-7)	2B Possibly carcinogenic to humans. 1 Carcinogenic to humans. 2B Possibly carcinogenic to humans.
Carbon black (CAS 1333-8	86-4)	Known To Be Human Carcinogen.
Quartz (Crystalline silica) (		Known To Be Human Carcinogen.
OSHA Specifically Regulated		
Quartz (Crystalline silica) (	(CAS 14808-60-7)	Cancer
Reproductive toxicity	This product is not expected to	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	Toxic to aquatic life. Harmful to	o aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No data available.	
13. Disposal consideration	S	
Disposal instructions	material under controlled conc	in sealed containers at licensed waste disposal site. Incinerate the litions in an approved incinerator. Dispose of contents/container in //national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	product residues. This materia Disposal instructions).	local regulations. Empty containers or liners may retain some al and its container must be disposed of in a safe manner (see:
Contaminated packaging		retain product residue, follow label warnings even after container is ould be taken to an approved waste handling site for recycling or

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

## 15. Regulatory information

15. Regulatory information	n		
US federal regulations	Standard, 29 CFR 1910.120	s Chemical" as defined by the OSHA Hazard Communication 0. or exempt from the U.S. EPA TSCA Inventory List.	
TSCA Section 12(b) Ex	port Notification (40 CFR 707	′, Subpt. D)	
Not regulated.			
CERCLA Hazardous S	ubstance List (40 CFR 302.4)		
Diuron (CAS 330-54-1)		Listed.	
SARA 304 Emergency	release notification		
Not regulated.			
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)			
Quartz (Crystalline	silica) (CAS 14808-60-7)	Cancer	
		lung effects	
		immune system effects	
		kidney effects	
Toxic Substances Control			
Superfund Amendments and R	-	ARA)	
SARA 302 Extremely hazar	rdous substance		
Not listed.			
SARA 311/312 Hazardous chemical	Yes		
Classified hazard categories	Serious eye damage or eye Respiratory or skin sensitiza Carcinogenicity		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List			
Not regulated.			
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)			
Not regulated.			
Safe Drinking Water Act (SDWA)	Contains component(s) regu	lated under the Safe Drinking Water Act.	
US state regulations			
US. Massachusetts RTK - S	Substance List		
Carbon black (CAS 133 Diuron (CAS 330-54-1) Mica (CAS 12001-26-2) Quartz (Crystalline silica Titanium dioxide (CAS 1	a) (CAS 14808-60-7) 3463-67-7)		
•	d Community Right-to-Know	Act	
Carbon black (CAS 133 Diuron (CAS 330-54-1) Mica (CAS 12001-26-2)			
Quartz (Crystalline silica) (CAS 14808-60-7)			

Titanium dioxide (CAS 13463-67-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4) Diuron (CAS 330-54-1) Mica (CAS 12001-26-2) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

### US. Rhode Island RTK

Carbon black (CAS 1333-86-4) Diuron (CAS 330-54-1) Mica (CAS 12001-26-2) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

## 16. Other information, including date of preparation or last revision

Issue date	05-June-2020
Revision date	-
Version #	01
HMIS® ratings	Health: 2* Flammability: 0 Physical hazard: 0
List of abbreviations	DOT: Department of Transportation (49 CFR 172.101). IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. LOEC: Lowest observable effect concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.
References	HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity
Disclaimer	Masterchem Industries LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.