

LOCTITE PL PREMIUM MAX construction adhesive is ideal for any interior or exterior project where long term strength and durability are a must. **GREAT FOR:** Stairs • Railings Framing • Flooring • Landscaping • Decks • Tub surrounds

SPECIFICATIONS

ASTM D3498, APA AFG-01, ASTM C557
Greenguard Certified

PHYSICAL PROPERTIES

Shelf life: 18 months

Cure time: 24 hours

Coverage: 1/4" bead: Approx 28ft/cart

Application Range: 10°F - 120°F

Clean up: Mineral spirits

WARNING! Contains crystalline silica and silanes. May be harmful if inhaled or swallowed. Methanol is released during application and cure, which may affect the nervous system causing dizziness, headache or nausea. Use in a well ventilated area. Do not breathe vapors. Avoid eye and skin contact. Prolonged or repeated skin contact with uncured adhesive may cause an allergic reaction. Wear gloves and safety glasses when applying product. Remove contact lenses before using adhesive. Wash hands after using. **FIRST AID:** For eye contact flush with water for 15 minutes. Call a physician if irritation develops and persists. For skin contact, wash with soap and water. If affected by inhalation, remove to fresh air and get medical attention. If ingested, do not induce vomiting; call a physician or Poison Control Center immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

VOC: < 5% by wt (CARB); < 65 g/L (less water and exempts)

WORKS ON

- | | | |
|------------|-------------------|--------------|
| • Wood | • Stone | • Vinyl |
| • Laminate | • Marble | • PVC |
| • OSB | • Granite | • Foamboard |
| • Drywall | • Mirrors | • Tile |
| • Concrete | • Metal | • Ceramic |
| • Brick | • Stainless steel | • Porcelain |
| • Masonry | | • Fiberglass |

APPLICATION TIPS

- Surface should be clean and free of debris.
- Cut nozzle and puncture inner seal.
- Apply adhesive to one surface, press surfaces firmly together.
- Use mechanical support for 24 hours during cure; Cure time dependent on temperature and humidity.
- To assist curing on non-porous surfaces apply a mist of water to the adhesive prior to joining materials.
- See TDS for mirror and tub surrounds installation instructions.

NOT RECOMMENDED FOR

Marine applications; Areas permanently immersed in water. Polyethylene, polypropylene, or polytetrafluoroethylene (PTFE)

¡ADVERTENCIA! Contiene sílice cristalina y silanos. Puede ser dañino si se inhala o se ingiere. Durante la aplicación y el proceso de curado se libera metanol, el cual puede afectar el sistema nervioso ocasionando mareos, dolor de cabeza o náusea. Utilice en un área bien ventilada. No aspire los vapores. Evite el contacto con los ojos y la piel. El contacto prolongado o repetido de la piel con el adhesivo no curado puede causar una reacción alérgica. Utilice guantes y gafas de seguridad cuando aplique el producto. Retire los lentes de contacto antes de utilizar el adhesivo. Lávese las manos después de utilizar el producto. **PRIMEROS AUXILIOS:** En caso de contacto con los ojos, enjuague con agua durante 15 minutos. Llame a un médico si desarrolla irritación o si persiste. En caso de contacto con la piel, lave con agua y jabón. Si le ha afectado la inhalación, trasládese al aire fresco y obtenga atención médica. Si lo ingiere, no induzca el vómito; llame a un médico o a un centro de control de envenenamiento de inmediato. **NO INTRODUZCA EN EL CUERPO. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

COV: < 5% por peso (CARB); < 65 g/l (menos agua y compuestos exentos)

⚠ ADVERTENCIA: Cáncer y Daño Reproductivo – www.P65Warnings.ca.gov



Henkel Corporation
One Henkel Way
Rocky Hill, CT 06067
1-800-624-7767
loctiteproducts.com




GREENGUARD

PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



All rights reserved

MADE IN USA



0 79340 65214 9

©Henkel Corp., 2017/3082651 IDH# 2291960