

PRODUCT SPECIFICATIONS

* This kit comes with screws compatible with door thickness of 3/4" to 1 1/8".

* Mini Classic Design rollers gives the lowest clearance from the top of the door to the ceiling measuring only 4". That's all you need!

*For a Single Track Bypass there is a compulsory overlap of 2 5/8" (that is when the roller/hanger is installed to the very edge of the door on both side per door). If you install the roller 1" from the edge of the door that will make the overlap measurement to 4 5/8". If you like to look at the details you may download the instruction manual and look at page 5 for a diagram and explanation of how to calculate the compulsory overlap of two doors.

* This hardware kit comes with everything you need like anti jump pads, floor guides, door stoppers, lag bolts, screws all you need to mount the track to the wall and the door to the sliding hardware except for doors. You don't have to look elsewhere for extra pieces to put a sliding door together. Doors are not included.

* Tracks 24in, 30in, 36in, 42in, 48in, 60in, is one peice track with American Standard Spacing of 16in. Tracks not listed come with two or three pieces using a junction plate to connect, therefore the spacing between the two holes where the tracks connect may not be 16in.

*Our rollers are made out of strong Nylon specifically designed for a quiet rolling system.


*Material is made for indoor & outdoor use. We usually recommend to spray Rustoleum for longer lasting usage when installing outdoors.


*This hardware can hold up to 50lbs total door(s) weight used per kit.

*Installation will be provided with ONLY 12-STEP easy to follow instructions in the box.

If you have any questions please contact us at:

 info@homacer.com

 770-864-5437

 www.homacer.com