

4996TRM Tub/Shower/Hand Shower Trim Specification Submittal

Location:

Model Numbers

- ☐ **4996TRM**
Tub/Shower/Hand Shower Trim

Valve Options:

- 261 Series Temptrol® Shower Valve with TRM modifier
- 161 Series Temptrol Shower Valve requires TC modifier
- 3DIVBODYSRT 4-Port Diverter Valve

Feature Highlights


- Verity Tub/Shower/Hand Shower Trim.
- Requires Temptrol® Pressure-Balancing Shower Valve.
- Requires 4-Port Diverter valve.
- Metal lever handle.
- Slip-on tub spout.
- Standard 2.0 gpm (7.6 L/min) flow rate.
- Dual check valve for back flow.
- 30" slide bar.
- 60" flexible metal hose.
- Single-mode showerhead.
- Single-mode HydroMersion® hand shower wand with Non-Positive Shutoff (NPSO).
- Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish.

Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) 2.0 gpm (7.6 L/min)
- Lever handle meets ADA requirements for operation
- 1.5 gpm option meets CALGreen requirements




Options/Modifications

- ☐ **15**  1.5 gpm (5.7 L/min) flow restrictor
- ☐ **MB** Matte Black finish
- ☐ **STN** Satin Nickel finish
- ☐ **L1** Less showerhead
- ☐ **L2** Less hand shower
- ☐ **L3** Less showerhead and hand shower
- ☐ **L5** Less hand shower system
- ☐ **L7** Less handle
- ☐ **TC** Test Cap Trim (includes TA-10™ & T-12A) *used with 161 Series Temptrol Shower Valve*

Warranty

Limited Lifetime - for residential installations.
10 Years - for commercial/industrial installations.
Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder


Series	Finish	Modifier	Flow Rate	Trim (required)	Test Cap	Final SKU
4996	STN	L7	15	TRM		4996STNL715TRM
4996	MB			TRM	TC	4996MBTRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons _____ Includes Verity Tub/Shower/Hand Shower Trim for Temptrol Pressure-Balancing Shower Valve. Features metal lever handle, 30" slide bar for hand shower wand, dual checks for backflow protection, 60" flexible metal hose, slip-on tub spout, single-mode HydroMersion hand shower wand with NPSO, single-mode showerhead, and standard 2.0 gpm (7.6 L/min) flow restrictors. Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Lever handle and hand shower wand meets ADA requirements for operation. 1.5 gpm option meets CALGreen requirements. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, MB = Matte Black finish, STN = Satin Nickel finish, L1 = Less showerhead, L2 = Less hand shower, L3 = Less showerhead and hand shower, L5 = Less hand shower system, L7 = Less handle, TC = Test Cap Trim.

Dimensions



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for drywall, plaster, or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.