



**INSPIRE  
 FROSTED GLASS SPRAY**

**DESCRIPTION AND USES**

Rust-Oleum® Inspire Frosted Glass is a semi-transparent finish that obscures vision, but permits light to shine through painted objects. Ideal for use on glass doors, windows, skylights, exterior shower doors and greenhouses. For a decorative effect, use a stencil to create an etched look on mirrors, shower doors, glass accessories and more.

**PRODUCTS**

<b>SKU (11 ounces)</b>	<b>DESCRIPTION</b>
297069	Frosted Glass

**PRODUCT APPLICATION**

**READ ALL DIRECTIONS BEFORE BEGINNING PROJECT**

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**SURFACE PREPARATION**

Clean the surface with soap and water, rinse and let dry.

**PRODUCT APPLICATION**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more "wet" coats a few minutes apart for the best appearance. (A "wet" coat should appear shiny as it is applied to the surface). **WAIT 10 MINUTES FOR THE FROST EFFECT. Do not use near open flame.**

**DRY & RECOAT TIMES**

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. May recoat anytime. Dries completely in 5-10 minutes.

**CLEAN-UP**

When finished spraying, clear spray valve by turning the can upside down and pushing the spray button for 5 seconds. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not stick pin or other objects into the stem.

**NOTE:** Frosted surfaces may be cleaned with a household glass cleaner and soft cloth or hand washed with liquid soap and water. Do not place items in a dishwasher. To remove frosted finish from glass, use lacquer thinner or acetone.

**TECHNICAL DATA**

**FROSTED GLASS SPRAY**

**PHYSICAL PROPERTIES**

		FROSTED GLASS SPRAY
<b>Resin Type</b>		Acrylic Polymer
<b>Pigment Type</b>		Amorphous Precipitated Silica
<b>Solvents</b>		Acetone, n-Butyl Acetate, Naphtha, Xylene
<b>MIR</b>		1.35 Max
<b>Fill Weight</b>		11 ounces
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		1.0-2.0 mils (25-50 $\mu$ )
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		8-12 sq.ft./can (0.74-1.11 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Recoat</b>	Anytime
	<b>Fully Dry</b>	5-10 minutes
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-141°F (-96°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.