



SPECIFICATIONS

BFQ50

EXHAUST FANS



50 CFM/0.6 Sones @ 0.10" SP.
36 CFM @ 0.25" SP.

• Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".

• Blower Wheel

One piece polymeric wheel 5¹/₈" diameter, 2³/₈" wide, with 48 fins.

• Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

• Fan Housing

PC/ABS polymeric, dimensions 8¹¹/₁₆" x 9¹/₈" x 4³/₄".

• Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

• Ventilating Area

For bathrooms up to 45 sq. ft. For other rooms up to 60 sq. ft.

• Single Pack Shipping Info

Box Dim: 11" x 12" x 6"
 UPC: 0-8316225021-6
 Shipping Weight: 5¹/₄ lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



• Unit Mounting

Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8¹/₁₆" x 9¹/₈".

EXPANDED PERFORMANCE

	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	56	53	50	48	47	42	36	0.6	1225	17.4	0.3

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY			DATE	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: 820 Lincoln Avenue
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada:
 Brampton, Ontario
 Tel: 800-250-8767
 Fax: (905) 456-1015