

**Model 64 UL Listed Wire Combinations Strip Wires 5/8 in.
UL File Number E5238**

Copper to Copper wire only (do not use on aluminum).



600 Volt Maximum. For use with solid or stranded combinations

3 or 4 #22 solid	1 #18 w/ 1 to 2 #10	1 #14 solid w/ 1 or 3 #12	1 #16 w/ 1 or 2 #14 w/ 1 #12 or 10
3 or 4 #20 solid	2 #18 w/ 1 to 3 #16, 14, 12	1 #14 w/ 1 or 2 #10	1 #16 w/ 1 #12 w/ 1 #10
2 to 4 #18 solid	2 #18 w/ 1 to 2 #10	2 #14 w/ 1 to 2 #12	2 #16 w/ 1 #14 w/ 1 or 2 #12
2 to 4 #16	3 #18 w/ 1 to 2 #16, 14, 12	2 #14 w/ 1 to 2 #10	2 #16 w/ 2 #14 w/ 1 #12
2 to 5 #14	3 #18 w/ 1 or 2 #10	2 #14 w/ 1 #8	2 #16 w/ 1 #12 w/ 1 #10
1 to 3 #12	1 #16 w/ 1 to 4 #14, 12	3 #14 w/ 1 #12 or #10	3 #16 w/ 1 #14 w/ 1 #12 or 10
4 #12 sol.	1 #16 w/ 1 to 2 #10	3 #14 w/ 2 #12	1 #14 w/ 1 or 2 #12 w/ 1 #10
1 to 3 #10	2 #16 w/ 1 to 4 #14	4 #14 w/ 1 #12 or 10	2 #14 w/ 1 #12 w/ 1 #10
1 #20 solid w/ 1 to 4 #18 or 16	2 #16 w/ 1 to 3 #12	1 #12 w/ 1 or 2 #10	1 #22 solid w/ 1 #18 w/ 1 #16
2 #20 solid w/ 1 to 3 #18 or 16	2 #16 w/ 1 to 2 #10	1 #12 w/ 1 #8	1 #22 solid w/ 1 #20 solid w/ 1 or
3 #20 solid w/ 1 or 2 #18 or 16	3 #16 w/ 1 to 3 #14	2 #12 w/ 1 #10	2 #16
1 #18 w/ 1 to 4 #16, 14, 12	3 #16 w/ 1 or 2 #12, 10	1 #10 w/ 1 #8	