

**FOR USE WITH ALL
CHAINSAWS**

**ENVIRONMENTALLY
FRIENDLY**

- HIGH TACK FORMULA HELPS
REDUCE SLING & THROW OFF
- ANTI-WEAR ADDITIVE TO
- HELP EXTEND BAR & CHAIN LIFE
- LOW TEMPERATURE
- PATENT PENDING
- RUST & CORROSION
INHIBITORS
- BIO BASED AND
BIODEGRADABLE
- NON-TOXIC
- CONTAINS NO PETROLEUM
INGREDIENTS



108 Daytona St.
Conway, SC 29526
(843) 347-0482



B3C 20-024

L2024-2



**KEEP OUT OF THE REACH OF CHILDREN.
SEE SDS FOR MORE INFORMATION.**

**24 FL OZ
(709.8 ML)**

INSTRUCTIONS: Drain all existing bar & chain oil. Do not mix MIB PLANT-BASED, BIODEGRADABLE BAR & CHAIN LUBRICANT with standard oil. Set your chainsaw on a level surface, bar side down so that it lays flat. Allow a minute for the lubricant to settle, then unscrew the cap to the saw's bar and chain lubricant reservoir. Using a small funnel, slowly pour the bar and chain lubricant into the reservoir, taking care not to overfill. For optimal results, store and use above 32F (32 degrees Fahrenheit). For more information visit www.B3CFuel.com.

Emergency Tel No USA:
INFOTRAC +1 (800) 535-5053
Emergency Tel No International:
INFOTRAC +1 (352) 323-3500
KEEP OUT OF REACH OF CHILDREN. SEE
SDS FOR MORE INFORMATION
HEALTH: May cause skin & eye irritation.
PRECAUTIONARY/RESPONSE: Wear
protective gloves & eyewear. IF ON
SKIN, rinse with water. IF IN EYES rinse
with water for at least 15 minutes. If
skin or eye irritation persists get
medical attention. Bar & Chain Lubricant
is slippery on floors creating a falling
hazard. Do not ingest or get in eyes.

Manufacturer's liability is limited to
replacement of product or refund of purchase
price upon return of unused portion and proof
of purchase.



WARNING Cancer -
www.P65Warnings.ca.gov