

**Lexel**  
**10.5 OZ - Cartridge**  
**CLEAR**  
**October - 2025**

Clear

sticks to  
**WET**  
surfaces

The Tough Elastic Sealant for Every Job

# Lexel®

Sticks to Almost Anything\*

Instantly waterproof • Cured sealant is mildew resistant • Paintable

↑ PUNCTURE ME HERE ↑

**L**exel® seals most everything – it's the "duct tape" of caulks. Interior & exterior use. Super-elastic. Excellent adhesion. Use on glass & showers, metals & gutters, wood & trim. It's tough. It's crystal clear. It won't let you down.

- Meets ASTM C920 Class 50 (See TDS for more info).
- Permanently flexible
- Super elastic - 747% stretch

**INSTRUCTIONS**

**Before you start:**

- Apply to clean surfaces, free of frost, oil & dirt.
- Application range: 0°F to 120°F (-18°C to 49°C).
- Tack free in 30 minutes.
- Cures completely in 1 to 2 weeks.

**Step 1.** Cut tip to desired bead size at a 45° angle. Puncture inner foil seal. Apply.

**Step 2.** Use soapy water or mineral spirits to smooth out bead for best adhesion.

**Step 3.** Clean up with citrus-based cleaners or mineral spirits.

**NOTE:** Paintable in 48 hours with latex paints or in 7 days with oil-based paints. Not for use in areas of prolonged submersion.

**INSTRUCCIONES**

**Antes de empezar:**

- Aplicar sobre superficies limpias, libres de hielo, aceite y suciedad.
- Campo de aplicación: 0°F a 120°F (-18°C a 49°C).
- Tacto en 30 minutos.
- Cura completamente en 1 a 2 semanas.

**Paso 1.** Corta la punta al tamaño deseado con un ángulo de 45 grados. Perfora el sello interior. Aplica.

**Paso 2.** Para lograr mayor adhesión alise la gota con agua jabonosa o aceites minerales.

**Paso 3.** Limpie con detergentes cítricos o aceites minerales.

**NOTA:** Se puede pintar en 48 horas con pinturas de látex o en 7 días con pinturas de aceite. No debe utilizarse en zonas de inmersión prolongada.

**USE ON:**

showers • tubs • sinks • tile • countertops  
backsplashes • cables • sills • drywall  
windows • doors • moulding • trim  
skylights • siding • wallpaper  
thresholds • shingles • vents  
ductwork • HVAC • eaves • gutters  
flashing • pavers • retaining walls  
endless possibilities!

**\*STICKS TO:**

itself • acrylic • copper • steel • aluminum  
chrome • metal • nylon • fiberglass  
terra-cotta • Plexiglas® • PVC  
most plastics • ABS • polycarbonate  
brick • polystyrene (not foam) • tile  
porcelain • parquet • asphalt  
masonry • Formica® • Lexan® • stone  
glass • vinyl • canvas • paint • concrete  
wood • fiber cement • & MORE!

**DANGER: VAPOR HARMFUL.**

**FLAMMABLE. EYE & SKIN IRRITANT.** Do not swallow. Do not breathe fumes. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.** Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area.

Contains toluene.

**FIRST AID:** If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

**WARNING:** This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

VOC Content: 380g/L, 43% by wt.

**Limited Lifetime Warranty:** For a detailed description of the warranty & exclusions, visit [www.sashco.com](http://www.sashco.com).

**DANGER**  
VAPOR HARMFUL.  
FLAMMABLE. IRRITANT.  
Read cautions on back label carefully.  
10.5 FL. OZ. (310 mL)

©2025 Sashco, Inc.  
Thornton, CO 80023  
800-767-5656  
[sashco.com](http://sashco.com)  
Family Owned.  
Colorado Made.  
Since 1936.

PKG030198  
LXLCLCTGVOC0925