

Cool tones, like those available from Erosion™ porcelain tile collection, remain the standard in interiors and exteriors. Their aesthetic appeal, coupled with the durability of tile, makes for a strong foundation in design. Available in three sizes, Erosion features the beauty found in nature.

EROSION™

Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  OUTDOOR  POOL 



Glacier



Rock




Valley




Wind


Mosaics




Glacier








Rock



Valley




Wind

Sizes							
	20" x 20" 19.57" x 19.57"	13" x 13" 12.99" x 12.99"	12" x 24" 11.81" x 23.62"	12" x 12" Mesh 11.69" x 11.69"	3" x 12" Floor SBN		
Thickness	8.5mm	7.1mm	8.4mm	9mm	Check Webiste		
Faces	16	20	16	N/A	N/A		
Finish	Matte	Matte	Matte	Matte	Matte		
Edge	Pressed	Pressed	Pressed	Cut	Cut		
Grout Joint Recommendation	3/16"	3/16"	3/16"	Check Webiste	Check Webiste		
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
	IV	>350 lbf (12x24, 20x20) >250 lbf (13x13)	Resistant	<0.50%	>0.60	9	V2

Product and Installation Details | ANSI A108.02
Section 4.3.8.2 - For running bond/brick joining patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC <0.5 mg/m³
- Recycled Content 3-4% Pre-Consumer and 72% Post-Consumer for Packaging Cartons

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.