







2 SLIDE LOCKS-#2117 Ports are identical and have "T" finger pulls for easy operation when correctly installed. They slide in, to lock the table top in place and slide out, to go to the bench mode.






Of HBE

If your 2x4's are not already cut to size:


Lay all nine 2x4's on the ground, square the ends so all are the same length.

With all 2x4's now the same length, cut two 2x4's 12 1/2" shorter. Set these shorter 2x4's aside for later use.

IF YOU ARE PLANNING TO PAINT OR FINISH THE LUMBER, NOW IS THE BEST TIME TO DO IT.




Lay four long 2×4's on the ground, ends squared. *Place the Pivots, "FRONTS" (open end) to you, o *Place the Pivots, "FRONTS" (open end) to you, on top of the 2x4's and 5" in from the ends. Make sure the outer 2x4's are flush with the front and back of the Pivots and squared at the ends. Space the inner 2x4's serely (about 1½" apart, or approximately the width of a pencil). Drill pilot holes into 2x4's through screw holes in pivots and fasten with 16 of the screws provided.




Firmly snap Slide Locks into Pivot Lock Slots. Slide Locks should slide freely in slots and close completely.

ATTENTION: IF THE PIVOTS AND SLIDE LOCKS ARE NOT CORRECTLY POSITIONED, THE CONVERTING TABLE WILL NOT WORK PROPERLY.



Insert the two shorter 2xA's(stringer boards) cut in Step 1 into their holes in the legs of both Bench Ends as shown. (NOTE: There are rounded tabs in the bottom of these holes that help to correctly position these 2xA's).

ATTENTION: DO NOT SECURE THE STRINGER BOARDS TO THE LEGS AT THIS TIME.




Make sure the Slide Locks are in the open position and the front (open slide


Make sure the Stide Locks are in the open position and the front (open slide lock end) is installed exactly as shown in the above Diagram!

Fit tops of Bench Ends into Pivots. Secure as shown with Pivot Bolts and Jam Nuts provided. Turn the Bench upright.

NOTE: The Jam Nuts are locking-type so they do not loosen after assembly, and will tighten with some difficulty. Use Wrenches to make certain Jam Nuts are snug in order to avoid wobble in the table top. (Do not over tighten, typically when one thread shows out of the Jam Nut, it is tightened properly.)



Align the ends of the stringer boards **flush to the end of the holes** in the legs of the Bench Ends. Drill pilot holes into 2x4's at **all** of the screw slots, inside and outside, of both legs and fasten with 8 of the screws provided.



To make the seat, position the first of the remaining three 2x4's at the front edge of the Bench Ends, and squared with the table top. Fasten underneath through the screw slots, inside and out, with 12 of the screws provided. Position and fasten the last (2) 2×4's, squared and spaced about 1/4" apart.


CONGRATULATIONS! YOUR CONVERTING TABLE IS NOW COMPLETED AND READY TO ENJOY!

To convert to a table: Flip top up and push the Slide Locks inward until they snap into place, flush with pivot.

To convert to a Bench: Pull the Slide Locks fully front, and then flip the

NOTE: We have provided a notch in the back of the pivot if you wish to secure two Converting Tables together to make a full-size picnic table. If you choose to do this, insert a 5 /s" x 1 /s" bolt (not included) through the notches of the matched Pivots and secure with a 5 /te" nut (not included).


To Use As A Table.



To Use As A Bench.



To Use As A Picnic Table...




2-Year Limited Warranty for this 2x4basics product purchased for normal household use. Hopkins Mfg. warrants this product to the original purchaser of a Hopkins Mfg. product that it will be free from defects in material and workmanship for a period of 2 years from the date of purchase. Hopkins Mfg. will repair, replace, or refund the purchase price of the product, at the option of Hopkins Mfg., upon return of the product and the original receipt. In the US, this warranty gives you specific legal rights that may vary from state to state.



428 Peyton St. Emporia, KS 66801 800-524-1458







R













